



- ▶ Odorless
- ▶ Water Based, Paintable
- ▶ Easy Gunability
- ▶ 1 year Shelf Life
- ▶ Red Color
- ▶ UL Classified
- ▶ Zero VOC's
- ▶ Unaffected by Freeze/Thaw
- ▶ Adhesion to almost Any Surface
- ▶ Non-Corrosive & Non-Combustible
- ▶ Non-Toxic - Environmentally Safe

- ▶ Non-Combustible Firestopping Caulk
- ▶ UL Classified for 1 & 2 Hour Fire Rated Walls & Floors
- ▶ Forms a Barrier to Prevent the Spread of Flames, Smoke & Toxic Fumes
- ▶ One Part Non-Intumescent Silicate based Firestop Sealant
- ▶ Tested & Approved for Use as Filler for Through Penetration Firestop Systems
- ▶ Meets Fire/Draft/Smoke criteria for BOCA – CABO – UPC – SBCC/IRC
- ▶ Suitable for Commercial, Industrial & Residential Firestop Requirements
- ▶ ASTM E-84 0 Flame & 0 Smoke Certified
- ▶ ASTM E-136 Residential Use Certified
- ▶ ASTM E-814 Commercial Use Compatible

Cat. No.	Description	Case Qty
67090	10.5 oz. Tube	12
99982	29oz. Tube	12
99984	1 Gallon Pail	1
99986	5 Gallon Pail	1

## Silicone Sealant



- ▶ 100% Silicone Adhesive Sealant
- ▶ Seals electrical components & provides weather-tight closure for electrical boxes & exterior fixtures
- ▶ Acetic cure anti-fungus Acetoxy based silicone sealant suitable for construction & household repairs
- ▶ Exhibits an excellent sealing and adhesion to metal, glass, tiles, ceramics, fiberglass, aluminum, non-oily wood, painted surfaces, plastic, rubber, fiber & other non-porous materials
- ▶ Protects & seals - waterproof & flexible - indoors & outdoors
- ▶ Fills voids & irregularities. Not paintable
- ▶ RTV 100% Silicone, flexible from -60°F to 450°F, 20°F min dispensing temp.
- ▶ High Temperature Sealant rated from -85°F to 500°F meets Federal Spec. TT-S-001543A
- ▶ Meets FDA Reg. #21 CFR 177.2600, Federal Spec. TT-S-00230C, MIL-A-46106A Amend. 2, ASTM C-920
- ▶ Complies with EcoSeal Standards, LEED 2009, NAHB Green Guidelines, SCAQMD Rule #1168 OTC, CARB, BAAQMD
- ▶ 10.3oz Tubes

Cat. No.	Color	Case Qty
99912	Clear	12
99916	White	12
99913	Silver	12
99914	Black	12

### Hi-Temp Silicone

99911	Red	12
-------	-----	----