



AF7503

Any Flow Frost Proof Yard Hydrant

Submittal Data



AF7503



BVBADNL75

Job or Customer _____

Engineer _____

Contractor _____

Submitted by _____ Date _____

Approved by _____ Date _____

Purchase Order Number: _____

Date Required: _____

Cut Away View - Shows the plunger inside the valve body

Technical Data - Hydrant

AF7503 - Standard Any Flow Frost Proof Yard Hydrant

Inlet - 3/4" NPT in Heavy Casting

Outlet - 3/4" Brass Hose Thread

Stainless Steel Operating Rod Thru Teflon Packing

Automatic Self-Adjusting Plunger

1" Galvanized Stand Pipe

7/16" Galvanized Operating Rod

Bury Depth - 3'

Technical Data - Vacuum Breaker

BVBADNL75 - No Lead Brass Vacuum Breaker

3/4" Hose

No Lead Brass Finish

Automatic Drain

ASSE-IAPMO Code approved and marked

Any Flow 3/4" Flow Rates

WATER SYSTEM PRESSURE	GALLONS PER MINUTE (GPM)											
	0	5	10	15	20	25	30	35	40	45	50	
20 PSI	18 GPM @ 20 PSI											
30 PSI	21 GPM @ 30 PSI											
40 PSI	24 GPM @ 40 PSI											
60 PSI	30 GPM @ 60 PSI											
80 PSI	34 GPM @ 80 PSI											
100 PSI	40 GPM @ 100 PSI											

NOTE: Most common 1/2 hp submersible pumps output is 10GPM.



315 Flindt Drive
P.O. Box 392
Storm Lake, Iowa
50588-0392 U.S.A.

Main # (712) 732-2760
U.S. & Canada # (800) 831-6962

Fax # (712) 732-4401
U.S. Fax # (800) ANY FLOW
www.merrillmfg.com