


## Rubber/Cork Anti-Vibration Pad

- Highest quality elastomeric oil resistant padding.
- Designed to withstand 50 psi.
- Rubber pads are corrugated on both sides.
- Cork is laminated between two corrugated pads.
- Ideal for air conditioners, compressors, cooling towers, presses, machines, etc.




TMP-4C

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TMP-2C	2" X 2" X 7/8" RUBBER/CORK	EA	1
TMP-3C	3" X 3" X 7/8" RUBBER/CORK	EA	1
TMP-4C	4" X 4" X 7/8" RUBBER/CORK	EA	1
TMP-6C	6" X 6" X 7/8" RUBBER/CORK	EA	1

## E.V.A. Anti-Vibration Pad

The latest generation in vibration dampening technology. The most effective vibration dampening pad available on the market. The EVA Pad was tested against other pads at four different vibration settings. In the most severe vibration extremes, the EVA Pad outperforms cork and rubber by a margin of greater than 3:1

- Special composite foam center which is much more structurally sound than cork.
- Not affected by oils or chemicals that can break down cork
- More effective at vibration dampening than solid rubber.
- Designed to withstand 50 PSI.



TMP-4E

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TMP-2E	2" X 2" X 7/8" E.V.A. PAD	EA	1
TMP-3E	3" X 3" X 7/8" E.V.A. PAD	EA	1
TMP-4E	4" X 4" X 7/8" E.V.A. PAD	EA	1
TMP-6E	6" X 6" X 7/8" E.V.A. PAD	EA	1

## Hef-T-Foot™

The Hef-T-Foot™ is used to support small pipework, runs of cable tray, or an alternative to supporting condensing units, air source heat pumps or a variety of outdoor equipment.

- Hef-T-Foot™ with strut comes in four lengths: 9.8", 15.7", 23.6", 39.4"
- Manufactured from heavy duty recycled rubber
- Complete with .8" x 1.6" galvanized steel strut adhered to the rubber with industrial adhesive.
- Strong and durable rubber with drain slots moulded into the underside to allow standing water to flow under the foot.



TFF-250-S



TFF-250-UNI

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TFF-250-S	HEF-T-FOOT™ - 9.8" WITH 1.6" X .8" STRUT	EA	1
TFF-400-S	HEF-T-FOOT™ - 15.7" WITH 1.6" X .8" STRUT	EA	1
TFF-600-S	HEF-T-FOOT™ - 23.6" WITH 1.6" X .8" STRUT	EA	1
TFF-250-UNI	HEF-T-FOOT™ - 9.8" UNIVERSAL	EA	1

## Furnace Mounting Block

- Mounting block can support 40% more weight than competitive products - over 500 pounds
- Easy peel and stick installation.



TFB-I

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TFB-I	FURNACE MOUNTING BLOCK	EA	72