

Push-In Wire Connectors



- ▶ OEM Lighting Manufacturing
- ▶ Junction Boxes
- ▶ Control Panels
- ▶ Security/Alarm Systems
- ▶ Prefabricated Wiring Systems
- ▶ Lighting Retrofits

No Twisting! Just Push-in! Quick & Safe! Reduce Installation Costs!

Easy Installation:



1. TURN OFF POWER.
Strip wire approximately 0.45 inches. The strip length is marked on the connector.



2. Push the stripped stranded or solid conductor into the port of connector completely. No more twisting or taping.



3. Use a voltage tester to test your connection via the port on the connector

- ▶ **Accepts Stranded or Solid Conductors**
- ▶ Easy to Install - instead of twisting or taping, simply push wires into connector ports -saves you time and money
- ▶ Low wire insertion force allows fast, easy connections
- ▶ No-twist connection reduces repetitive motion fatigue
- ▶ See-thru for visual connection inspection
- ▶ Test port for continuity testing
- ▶ Electrolytic Tin-Plated Copper internal bus for high conductivity
- ▶ Housing Material: Thermoplastic, UL 94V-2 flame retardant
- ▶ Current: 24A (VDE)
- ▶ Voltage: UL-600V, VDE-450V
- ▶ Working Temperature: 230°F (110°C)
- ▶ Wire Range: 12-22 AWG
- ▶ Color Coded according to number of poles
- ▶ UL listed for Copper Conductors only

Dimensions = Inches

Cat. No.	Poles	Color	L	W	H	Qty	Case Qty
----------	-------	-------	---	---	---	-----	----------

Hanging Bag 25 Pack

23222	2	Red	.768	.413	.374	25	1,250
23223	3	Orange	.776	.531	.374	25	1,250
23224	4	Yellow	.776	.677	.374	25	1,250
23225	5	Gray	.776	.831	.374	25	1,250
23228	8	Black	.748	.689	.661	25	1,250


Boxed

23012	2	Red	.768	.413	.374	100	10,000
23013	3	Orange	.776	.531	.374	100	6,000
23014	4	Yellow	.776	.677	.374	100	6,000
23015	5	Gray	.776	.831	.374	100	6,000
23018	8	Black	.748	.689	.661	50	3,000

Bagged 100 Pack

23025	5	Gray	.776	.831	.374	100	5,000
23028	8	Black	.748	.689	.661	50	2,500

Ceramic Wire Connectors



- ▶ For Use in Appliances, High Power Lighting, Heaters, and High Temperature Applications
- ▶ Excellent Heat and Electrical Resistant Properties
- ▶ Working Temperature up to 1000°F Maximum
- ▶ Best for Applications above 200°F
- ▶ White

Dimensions = Inches

Cat. No.	Material	Conductor Range	Dimensions			Bag Qty	Master Box
			A	B	C		
23030	Ceramic	#22 - #14	.215	.375	.665	100	1500
23031	Ceramic	#22 - #10	.315	.567	.784	100	2500
23032	Ceramic	#18 - #8	.410	.715	1.025	100	7500