



Catalog Number 23012 - 23228
UPC Number
Description Push-In Wire Connector

Features

- Easy to Install - instead of twisting or taping, simply push wires into entry ports
- Low wire insertion force needed allows fast, easy connections
- No-twist connection reduces repetitive motion fatigue
- Re-useable making changes easy and reducing waste of connectors
- Clear housing for connection confirmation
- Check port for continuity testing
- Electrolytic tin-plated internal copper bus for high conductivity
- Housing material: Thermoplastic, Flame Retardant UL 94V-2

General

Material: Polycarbonate Thermoplastic, UL 94V-2
Electrolytic tin-plated internal copper bus; Stainless Spring Steel Clamp
Zinc-plated Steel Frame

Dimension Information

See Table

Specifications

Flammability Rating: UL 94V-2
Temperature Rating: 230°F (110°C)
Voltage Rating: 600V
Conductor Range: 22-12AWG, Sol / Str Cu
Strip Length : 11 mm / 0.43 in.

Packaging

Bag Qty See Table

Certifications

UL UL 486C
CSA CSA 22.2 #188
ROHS Yes

No.	Poles	Color	L	W	H	Qty	Case Qty
Hanging Bag 25 Pack							
23222	2	Yellow	0.768	0.413	0.374	25	1250
23223	3	Orange	0.776	0.531	0.374	25	1250
23224	4	Clear	0.776	0.677	0.374	25	1250
23225	5	Blue	0.776	0.831	0.374	25	1250
23228	8	Black	0.748	0.689	0.661	25	1250
Boxed 100 Pack							
23012	2	Red	0.768	0.413	0.374	100	10,000
23013	3	Orange	0.776	0.531	0.374	100	6,000
23014	4	Yellow	0.776	0.677	0.374	100	6,000
23015	5	Gray	0.776	0.831	0.374	100	6,000
23018	8	Black	0.748	0.689	0.661	50	3,000
Bagged 100 Pack							
23022	2	Red	0.768	0.413	0.374	100	5,000
23023	3	Orange	0.776	0.531	0.374	100	5,000
23024	4	Yellow	0.776	0.677	0.374	100	5,000
23025	5	Gray	0.776	0.831	0.374	100	5,000
23028	8	Black	0.748	0.689	0.661	100	2,500

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804