
DRAIN COCKS

- For use with low pressure air, water and fluids.
- Install on your tank for easy draining
- Designed for a working pressure of 150 psi @ 250°.
- Hand-tightening provides a metal-to-metal seal.
- Not intended for natural gas, LPG, nuclear or aircraft applications.


GASOLINE SHUT OFF w/ SCREEN FILTER



Part #	Barb X Male Pipe	A	В	C	Approx. Wt. Lbs.	List Price
46-064	1/4" x 1/8"	0.55	1.34	0.66	0.06	81.74

827

DRAIN COCK 150 PSI - Trunk Air Tank



Part #	Male Pipe	A	В	Approx. Wt. Lbs.	List Price
46-066	1/4"	1.73	1.41	0.22	26.18


DCR601-4

TRUCK DRAIN - 125 P.S.I.G



	Part #	Male Pipe	Industry Number	A	В	Hex	Approx. Wt. Lbs.	List Price
I	46-067	1/8"		1.53	1.95	0.62	0.14	18.94
Ī	46-068	1/4"	W15310	1.53	1.95	0.62	0.18	18.95

SHUT OFF - 150 P.S.I max.




Part #	Male Pipe x Female Pipe	Industry Number	A	В	Hex 1	Hex 2	Approx. Wt. Lbs.	List Price
46-069	1/4"	W20332	1.96	1.96	0.75	0.62	0.20	14.58

LOWER

#60HC 3380-A 0903610 367

840 41D DC601

LEVER HANDLE



Part #	Male	Industry	A	В	Hex	Approx.	List Price
	Pipe	Number				Wt. Lbs.	
46-070	1/8"	M-41-P	1.99	1.80	0.62	0.04	15.12
46-071	1/4"	M-42-P	2.06	1.81	0.62	0.06	12.69
46-072	3/8"	M-43-P	2.30	2.29	0.81	0.08	18.48
46-073	1/2"	M-44-P	3.00	2.50	0.87	0.16	51.46

LOWER

AIR TANK DRAIN PULL VALVE



Part #	Size	Description	List Price
39595	1/4" male	5ft nylon coated pull cable	12.77
39596	1/4" male	4ft nylon coated pull cable	11.94
39597	1/4" male	3ft nylon coated pull cable	11.77
39600	1/4" male	Air valve only	11.54

^{• 30} psi

^{*}Valve is closed when handle is in the position of the picture