



Copper Short Barrel 2 Hole Compression Lugs



- High Conductivity Seamless Copper
- Electro-Tin Plating Resists Corrosion, reduces Contact Resistance for Maximum Conductivity
- Dual Mounting Holes
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486A Listed for Applications Thru 35KV



Dimensions = Inches

Cat. No.	Wire Range	Stud Size	Hole Spacing	Color Code	ID	OD	A	A1	B	C	D	E	F	G	Box Qty
94110	8 Str.	#10	5/8	Red	.173	.272	1.82	.44	.42	.08	.21	.28	1.26	.63	50
94112	8 Str.	1/4	5/8	Red	.173	.272	1.82	.44	.42	.08	.25	.28	1.26	.63	50
94114	8 Str.	3/8	1	Red	.173	.272	1.82	.44	.42	.08	.41	.38	1.81	1.00	50
94116	6 Str.	#10	11/16	Blue	.205	.298	2.64	.71	.42	.08	.21	.28	1.26	.63	50
94118	6 Str.	1/4	5/8	Blue	.205	.298	2.64	.71	.42	.08	.25	.28	1.26	.63	50
94120	6 Str.	1/4	1	Blue	.205	.298	2.64	.71	.42	.08	.25	.28	1.81	1.00	50
94122	6 Str.	3/8	1	Blue	.205	.298	2.64	.71	.42	.08	.41	.38	1.81	1.00	50
94124	4 Str.	1/4	5/8	Gray	.252	.342	2.68	.75	.49	.09	.25	.28	1.26	.63	50
94126	4 Str.	1/4	1	Gray	.252	.342	2.68	.75	.49	.09	.25	.28	1.81	1.00	50
94128	4 Str.	5/16	1	Gray	.252	.342	2.68	.75	.49	.09	.33	.38	1.81	1.00	50
94130	4 Str.	3/8	1	Gray	.252	.342	2.68	.75	.49	.09	.41	.38	1.81	1.00	50
94132	2 Str.	1/4	5/8	Brown	.315	.421	2.28	.83	.60	.10	.25	.28	1.26	.63	25
94134	2 Str.	1/4	3/4	Brown	.315	.421	2.36	.83	.60	.10	.25	.28	1.38	.75	25
94136	2 Str.	1/4	1	Brown	.315	.421	2.80	.83	.60	.10	.25	.28	1.81	1.00	25
94138	2 Str.	5/16	3/4	Brown	.315	.421	2.62	.83	.60	.10	.33	.38	1.81	.75	25
94140	2 Str.	3/8	1	Brown	.315	.421	2.83	.83	.60	.10	.41	.38	1.81	1.00	25
94142	2 Str.	1/2	1-3/4	Brown	.315	.421	2.80	.83	.60	.10	.51	.62	2.99	1.75	25
94144	1 Str.	1/4	5/8	Green	.358	.468	2.28	.83	.67	.11	.25	.28	1.26	.63	25
94146	1 Str.	5/16	1	Green	.358	.468	2.28	.83	.67	.11	.33	.38	1.81	1.00	25
94148	1/0	1/4	3/4	Pink	.389	.519	2.64	.83	.74	.12	.25	.28	1.38	.75	10
94150	1/0	5/16	7/8	Pink	.389	.519	2.64	.83	.74	.13	.33	.32	1.62	.87	10
94152	1/0	3/8	1	Pink	.389	.519	2.83	.83	.74	.13	.41	.38	1.81	1.00	10
94154	1/0	1/2	1-3/4	Pink	.389	.519	2.83	.83	.74	.13	.51	.62	2.99	1.75	10
94156	2/0	1/4	3/4	Black	.440	.562	2.99	.94	.81	.11	.25	.28	1.38	.75	10
94158	2/0	5/16	7/8	Black	.440	.562	2.99	.94	.81	.11	.33	.32	1.62	.87	10
94160	2/0	3/8	1	Black	.440	.562	2.99	.94	.81	.11	.41	.38	1.81	1.00	10
94162	2/0	1/2	1-3/4	Black	.440	.562	4.17	.94	.81	.11	.51	.62	2.99	1.75	10
94164	3/0	5/16	1	Orange	.492	.622	3.11	.98	.90	.12	.33	.32	1.81	1.0	10
94166	3/0	3/8	1	Orange	.492	.622	3.11	.98	.90	.12	.41	.38	1.81	1.00	10
94168	3/0	1/2	1-3/4	Orange	.492	.622	4.29	.98	.90	.12	.51	.62	2.99	1.75	10
94170	4/0	5/16	1	Purple	.547	.688	3.11	.98	1.00	.13	.33	.32	1.81	1.00	10
94172	4/0	3/8	1	Purple	.547	.688	3.11	.98	1.00	.13	.41	.38	1.81	1.00	10
94174	4/0	1/2	1-3/4	Purple	.547	.688	4.29	.98	1.00	.13	.51	.62	2.99	1.75	10
94176	250	3/8	1	Yellow	.594	.751	3.22	1.06	1.09	.15	.41	.38	1.81	1.00	10
94178	250	1/2	1-3/4	Yellow	.594	.751	4.41	1.06	1.09	.15	.51	.62	2.99	1.75	10
94180	300	1/2	1-3/4	White	.657	.814	4.41	1.06	1.19	.15	.51	.62	2.99	1.75	10
94182	350	3/8	1	Red	.700	.874	3.35	1.10	1.28	.17	.41	.38	1.81	1.00	10
94184	350	1/2	1-3/4	Red	.700	.874	4.53	1.10	1.28	.17	.51	.62	2.99	1.75	10
94186	400	1/2	1-3/4	Blue	.763	.948	4.69	1.18	1.39	.18	.51	.62	2.99	1.75	10
94188	500	3/8	1	Brown	.838	1.06	3.70	1.38	1.54	.22	.41	.38	1.81	1.00	6
94190	500	1/2	1-3/4	Brown	.838	1.06	4.88	1.38	1.54	.22	.51	.62	2.99	1.75	6
94192	600	3/8	1-3/4	Green	.925	1.18	4.96	1.50	1.72	.25	.51	.62	2.99	1.75	4
94194	600	1/2	1-3/4	Green	.925	1.18	5.04	1.50	1.72	.25	.51	.62	2.99	1.75	4
94196	750	1/2	1-3/4	Black	1.04	1.31	5.51	1.85	1.90	.27	.51	.62	2.99	1.75	4

Compression
Power Connectors

B4