



Strut to Beam Clamp with Square U-Bolt



- ▶ For 13/16" & 1-5/8" Channel
- ▶ Design load 1200lbs. when used in pairs
- ▶ Zinc Electroplate Finish

Cat. No.	Description	Box Qty
17462	Beam Clamp for 13/16" & 1-5/8" Channel	25

Strut to Beam Clamp with Square U-Bolt



- ▶ For 2-7/16" & 3-1/4" Channel
- ▶ Design load 1200lbs. when used in pairs
- ▶ Zinc Electroplate Finish

Cat. No.	Description	Box Qty
17464	Beam Clamp for 2-7/16" & 3-1/4" Channel	25

Strut Fitting Torque Values

The following are the torque values used for determining the load ratings of fittings when attached to channel framing as specified in the Metal Framing Manufacturers Association (MFMA) Standard #2

Thread Size	Torque		
	In. lb.	ft. lb.	Nm
1/4"	72	6	8.1
3/8"	228	19	25.8
1/2"	600	50	67.8

Beam Clamp Torque Values

For beam clamps or other applications the following torque values from Manufacturer's Standardization Society (MSS) SP-69 are recommended unless otherwise specified

Thread Size	Torque		
	In. lb.	ft. lb.	Nm
1/4"	40	3.3	4.5
3/8"	60	5.0	6.8
1/2"	125	10.4	14.1