

Thermostat Wire



T620-18-5

- Class 2 thermostat wire for indoor wiring.
- Soft drawn bare copper wire.
- Semi rigid PVC insulation.
- PVC overall jacket.
- Packaged on aluminum spool.
- Meets Subject 13 per Article 725, 1990 NEC.
- U.L. Listed.

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T620-18-2	18 AWG, 2 CONDUCTORS - 500 FT. SPOOL	EA	1
T620-18-3	18 AWG, 3 CONDUCTORS - 500 FT. SPOOL	EA	1
T620-18-4	18 AWG, 4 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-18-5	18 AWG, 5 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-18-6	18 AWG, 6 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-18-7	18 AWG, 7 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-18-8	18 AWG, 8 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-18-10	18 AWG, 10 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-20-2	20 AWG, 2 CONDUCTORS - 500 FT. SPOOL	EA	1
T620-20-3	20 AWG, 3 CONDUCTORS - 500 FT. SPOOL	EA	1
T620-20-4	20 AWG, 4 CONDUCTORS - 250 FT. SPOOL	EA	1
T620-20-8	20 AWG, 8 CONDUCTORS - 250 FT. SPOOL	EA	1

High Temperature Wire, 400°F (204°C), 600 V.



- 7 strand tin coated copper wire.
- Silicone rubber insulation.
- Braided fiberglass jacket.
- Use on the front of all gas furnaces with spark ignition because of flame roll out on start up.
- Also on all power feeds to electric strip and duct heaters.
- Also used on all heat producing food preparation equipment.
- U.L. Listed.

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
TWHTB14-50	14 GAUGE, BLACK, 50 FT.	EA	1
TWHTR14-50	14 GAUGE, RED, 50 FT.	EA	1
TWHTW14-50	14 GAUGE, WHITE, 50 FT.	EA	1
TWHTB12-50	12 GAUGE, BLACK, 50 FT.	EA	1
TWHTB10-20	10 GAUGE, BLACK, 20 FT.	EA	1
TWHTB10-50	10 GAUGE, BLACK, 50 FT.	EA	1