

Catalog Number UPC Number Description 73458 60198673458 LED Wet Location Combo Exit and Emergency Sign High Output Remote Capable Red Legend 120/277 Volt

# Features



Flame Retardant, UV-stabilized corrosion & impact resistant Polycarbonate Housing Clear Polycarbonate Cover Enclosure resistant to corrosive atmospheres, non-hazardous dust environment, hose-down water spray or splashing water Universal canopy provides top, end or back mount convenience 2 Face Plates for Side or Top Installation Universal K/O Pattern on back plate for wall mount Engineering Grade Rubber Gasketing Top and Side K/O's provided for conduit feed applications EZ Snap-out chevron directional indicators Remote Capable for upto 4 Heads(Base Unit + 2 Heads) Meets UL924 for Wet Locations, 5 Year Warranty

#### General

| Material:        | Polycarbonate Housing<br>Clear Polycarbonate Cover |
|------------------|--|
| Lamp Type:       | LED  |
| Battery :        | 3.6V 1800mAH Ni-MH                                 |
| Emergency Power: | 90 minutes for 4 Heads(Base Unit + 2 Heads)        |
|                  | 120 Minutes for 3 Heads(Base Unit + 1 Head)        |
|                  | 180 Minutes for 2 Heads(Base Unit)                 |



### **Dimension Information**

| Length: | 12-9/16" |  |
|---------|----------|--|
| Height: | 13-5/16" |  |
| Depth:  | 2-1/2"   |  |
|         |          |  |

## Specifications

0 10

| Amperage Rating:     | 35.3mA@120V  | 16.2mA@277V  |
|----------------------|--------------|--------------|
| Wattage Rating:      | 4.06W @ 120V | 4.30W @ 277V |
| Voltage Rating:      | 120/277      |              |
| Flammability Rating: | UL94V-2      |              |

### Packaging

| Box Qty        | 1 |
|----------------|---|
| Master Box Qty | 4 |

### Certifications

| UL    | 924 for Wet locations |
|-------|-----------------------|
| cULus | Yes                   |