



Take-Up

UCT 200 PTI Series Normal Duty Bearing Cast Iron Housing Set Screw Lock Metric and Inch Bores



Models Available

Part No.	Shaft Size d		Dimensions (mm) (in)															Bearing No.	Housing No.	Wt. kg
	mm	in	A	B	b	D	E	F	G	H	K	L	M	O	P	R	S			
UCT204-20MM UCT204-12	20	3/4	94 3.70	21 0.83	10.5 0.41	89 3.50	76 2.99	51 2.01	10 0.39	61 2.40	19 0.75	28.75 1.13	16 0.63	32 1.26	51 2.01	32 1.26	12 0.47	UC204-20MM UC204-12	T204	0.94
UCT205-25MM UCT205-14 UCT205-15 UCT205-16	25	7/8 15/16 1	97 3.82	24 0.94	12 0.47	89 3.50	76 2.99	51 2.01	10 0.39	62 2.44	19 0.75	31.78 1.25	16 0.63	32 1.26	51 2.01	32 1.26	12 0.47	UC205-25MM UC205-14 UC205-15 UC205-16	T205	1.02
UCT206-30MM UCT206-18 UCT206-19 UCT206-20	30	1-1/8 1-3/16 1-1/4	113 4.45	28 1.10	14 0.55	102 4.02	89 3.50	57 2.24	10 0.39	70 2.76	22 0.87	36.17 1.42	16 0.63	37 1.46	56 2.20	37 1.46	12 0.47	UC206-30MM UC206-18 UC206-19 UC206-20	T206	1.51
UCT207-35MM UCT207-20 UCT207-22 UCT207-23	35	1-1/4 1-3/8 1-7/16	129 5.08	30 1.18	15 0.59	102 4.02	89 3.50	64 2.52	13 0.51	78 3.07	22 0.87	40.37 1.59	16 0.63	37 1.46	64 2.52	37 1.46	12 0.47	UC207-35MM UC207-20 UC207-22 UC207-23	T207	1.87
UCT208-40MM UCT208-24	40	1-1/2	144 5.67	33 1.30	16.5 0.65	114 4.49	102 4.02	83 3.27	16 0.63	88 3.46	29 1.14	46.6 1.83	19 0.75	49 1.93	83 3.27	49 1.93	16 0.63	UC208-40MM UC208-24	T208	2.73
UCT209-45MM UCT209-26 UCT209-27 UCT209-28	45	1-5/8 1-11/16 1-3/4	144 5.67	35 1.38	17.5 0.65	117 4.61	102 4.02	83 3.27	16 0.63	87 3.43	29 1.14	47.8 1.88	19 0.75	49 1.93	83 3.27	49 1.93	16 0.63	UC209-45MM UC209-26 UC209-27 UC209-28	T209	2.88
UCT210-50MM UCT210-30 UCT210-31 UCT210-32	50	1-7/8 1-15/16 2	149 5.87	37 1.46	18.5 0.73	117 4.61	102 4.02	86 3.39	16 0.63	90 3.54	29 1.14	51 2.01	19 0.75	49 1.93	83 3.27	49 1.93	16 0.63	UC210-50MM UC210-30 UC210-31 UC210-32	T210	3.0
UCT211-55MM UCT211-32 UCT211-34 UCT211-35	55	2 2-1/8 2-3/16	171 6.73	38 1.50	19 0.75	146 5.75	130 5.12	95 3.74	19 0.75	106 4.17	35 1.38	52.4 2.06	25 0.98	64 2.52	102 4.02	64 2.52	22 0.87	UC211-55MM UC211-32 UC211-34 UC211-35	T211	4.67
UCT212-60MM UCT212-36 UCT212-38 UCT212-39	60	2-1/4 2-3/8 2-7/16	194 7.64	42 1.65	21 0.83	146 5.75	130 5.12	102 4.02	19 0.75	119 4.69	35 1.38	60.6 2.39	32 1.26	64 2.52	102 4.02	64 2.52	22 0.87	UC212-60MM UC212-36 UC212-38 UC212-39	T212	5.7
UCT213-65MM UCT213-40	65	2-1/2	224 8.82	44 1.73	22 0.87	167 6.57	151 5.94	121 4.76	21 0.83	137 5.39	41 1.61	61.6 2.43	32 1.26	70 2.76	111 4.37	70 2.76	26 1.02	UC213-65MM UC213-40	T213	7.68
UCT214-70MM UCT214-43 UCT214-44	70	2-11/16 2-3/4	224 8.82	46 1.81	23 0.91	167 6.57	151 5.94	121 4.76	21 0.83	137 5.39	41 1.61	67.3 2.65	32 1.26	70 2.76	111 4.37	70 2.76	26 1.02	UC214-70MM UC214-43 UC214-44	T214	7.74
UCT215-75MM UCT215-47 UCT215-48	75	2-15/16 3	232 9.13	48 1.89	24 0.94	167 6.57	151 5.94	121 4.76	21 0.83	140 5.51	41 1.61	68.5 2.70	32 1.26	70 2.76	111 4.37	70 2.76	26 1.02	UC215-75MM UC215-47 UC215-48	T215	8.51
UCT216-80MM UCT216-50	80	3-1/8	235 9.25	51 2.01	25.5 1.00	184 7.24	165 6.50	121 4.76	21 0.83	140 5.51	41 1.61	74.7 2.94	32 1.26	70 2.76	111 4.37	70 2.76	26 1.02	UC216-80MM UC216-50	T216	9.4
UCT217-85MM UCT217-52	85	3-1/4	260 10.24	54 2.13	27 1.06	198 7.80	173 6.81	157 6.18	29 1.14	150 5.91	48 1.89	78.6 3.09	38 1.5	73 2.87	124 4.88	73 2.87	30 1.18	UC217-85MM UC217-52	T217	12.06
UCT218-90MM UCT218-56	90	3-1/2	275 10.83	55 2.17	27.5 1.08	215 8.46	190 7.48	140 5.51	30 1.18	160 6.30	48 1.89	83.8 3.30	40 1.57	80 3.15	130 5.12	80 3.15	30 1.18	UC218-90MM UC218-56	T218	14.82
UCT220-100MM	100	--	295	60	30	240	215	160	30	180	47	79.5	40	80	130	90	28	UC220-100MM	T220	15.50

Note: Eccentric and Adapter Lock Bearings also available from stock.