


Bronze Ball Valves

three-piece body • full port • 316SS internal trim • 300 series external trim • blowout-proof stem • vented ball




600 PSI/41.4 bar non-shock cold working pressure
150 PSI/10.3 bar saturated steam♦

CONFORMS TO MSS SP-110


MATERIAL LIST

PART	SPECIFICATION
1. Handle Nut	300 Series Stainless Steel
2. Handle	300 Series Stainless Steel with Platisol Grip
3. Threaded Pack Gland	Brass ASTM B 16 Alloy C36000
4. Stem	Stainless Steel ASTM A 276 Type 316
5. Body	Bronze ASTM B 584 Alloy C84400
6. Packing	PTFE
7. Body End (2)	Cast Bronze ASTM B 584 Alloy C84400
8. O-Ring Seal (2)	Fluorocarbon Rubber
9. Seat Ring (2)	PTFE
10. Ball (Vented)	Stainless Steel ASTM A 276 Type 316 or ASTM A 351 Type CF8M
11. Thrust Washer	Reinforced PTFE
12. Body Bolts	300 Series Stainless Steel
13. Body Nuts	300 Series Stainless Steel


Note: valves are static grounded by a grounding washer. (not shown)



T-595-Y-66-SS
Threaded



T-595-Y-66-SS
NPT x NPT



DIMENSIONS—WEIGHTS—QUANTITIES

Size		Dimensions										T-595-Y-66-SS		Master
		A		B		C		D		E				
In.	mm.	In.	mm.	In.	mm.	In.	mm.	In.	mm.	In.	mm.	Lbs.	Kg.	Qty.
¼	8	2.50	64	1.81	46	.38	10	1.69	43	3.91	99	1.03	.47	50
⅜	10	2.50	64	1.81	46	.38	10	1.69	43	3.91	99	.98	.44	50
½	15	2.50	64	1.81	46	.50	13	1.69	43	3.91	99	1.03	.47	50
¾	20	3.00	76	1.94	49	.75	19	2.00	51	4.66	118	1.70	.77	30
1	25	3.69	94	2.50	64	1.00	25	2.25	57	4.66	118	2.82	1.28	20
1¼	32	4.09	104	2.69	68	1.25	32	2.75	70	6.69	170	3.96	1.80	10
1½	40	4.56	116	3.00	76	1.50	38	2.97	75	6.69	170	5.68	2.57	10
2	50	6.16	156	4.00	102	2.00	51	3.63	92	6.69	170	11.40	5.17	4
2½	65	6.84	174	5.00	127	2.50	64	4.09	104	8.00	203	21.07	9.56	2

Visit our website for the most current information

♦For detailed operating pressure, refer to pressure temperature chart on page 41.