



# SPECIFICATION SHEET

## 9150-52515



### 25 CAL/CM<sup>2</sup> HI-VIS ARC HOOD, LENS, BRACKET & HARD HAT

- Arc Rating: ATPV 25 cal/cm<sup>2</sup>
- PPE 3 (HRC 3)
- Incorporates UV and IR-absorbing ARC shield lens providing protection up to 25 cal/cm<sup>2</sup>; replaceable
- Green tint window is coated with a permanent anti-fog inner surface
- Lens is extended 3" from face to accommodate respiratory protection and help minimize lens fogging
- Lens meets ANSI Z87.1
- Supplied with dielectric safety helmet and hard hat adapter

### STANDARDS MET

- NFPA 70E 2012
- ASTM F1506-2010a
- OSHA 29 CFR 1910.269

### APPLICATIONS

- Electrical & Utilities
- Petrochemical, Gas & Oil
- Mining
- Welding
- Emergency Services

### CARE INSTRUCTIONS

**Hood:** Machine wash warm, 165°F max. Tumble dry low. DO NOT bleach. DO NOT use fabric softener. DO NOT iron.

**Lens:** Clean and inspect before and after use. Clean with a damp cloth unless heavily soiled. Should further cleaning be required, clean with mild soap and water, pat dry. Disassemble if required, for cleaning and inspection.

### TECHNICAL DATA

MATERIAL	Westex Ultrasoft 88% Cotton 12% High Tenacity Nylon
CONSTRUCTION	Multi-Layered: 7 oz FR Cotton over 7 oz FR Cotton
COLOR	■ Navy
SIZES	OSFM
PACKAGING	1/bag
CASE SIZE	16" x 16" x 12" / 40.6cm x 40.6cm x 30.5cm
CASE WEIGHT	5 lbs / 2.3 kg
COO	USA

### BARCODES

ITEM	BAG	BOX	CASE
■ 9150-52515			



### DIMENSIONS (in)

	OSFM						
A	32						

