

SPECIFICATION SHEET 280-HP341SR

DYNAMIC DOM SMOOTH DOME HARD HAT WITH SWING STRAP SUSPENSION

- Meets -ANSI/ISEA Z89.1 Type 1 and CSA Z94.1 Type 1 requirements
- Fulfills Class E Electrical Insulation requirements
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- SURE LOCK wheel adjustment system for one hand size adjustments
- Swing strap suspension enables the wear to reverse don the hat without having to reinstall the suspension
- Precise height adjustment settings to ensure proper depth
 Low nape strap provides a secure fit, allowing the hard hat to stay
- on your head even when workers are looking down or bending over
- Non-chaffing, replaceable foam sweatband for maximum sweat absorption
 Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Demolition
- Manufacturing
- Welding
- Energy companies
- Metalworking

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extreme temperatures.

TECHNICAL DATA

| MATERIAL | Shell: High Density Polyethylene Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE | |
|-------------|---|--|
| COLOR | □ White (-01) ■ Sky Blue (-07) ■ Red (-15) ■ Yellow (-02) ■ Navy Blue (-08) ■ Royal Blue (-17) ■ Orange (-03) ■ Gray (-09) ■ Steel Blue (-71) ■ Dark Green (-04) ■ Black (-11) ■ Forest Green (-74) | |
| SIZES | 6-8 (52cm-64cm) | |
| WEIGHT | 0.75 lbs / 0.34 kg | |
| PACKAGING | 12 per case | |
| CASE | 17.5" x 12.5" x 24.5" / 44.4cm x 31.75cm x 62.23cm | |
| CASE WEIGHT | 13.1 lbs / 5.95 kg | |
| C00 | Canada | |

BARCODES


| ITEM | EACH | CASE |
|----------------|--------------|----------------|
| 280-HP341SR-01 | 620606006581 | 10620606006588 |
| 280-HP341SR-02 | 620606006598 | 10620606006595 |
| 280-HP341SR-03 | 620606006604 | 10620606006601 |
| 280-HP341SR-04 | 620606006611 | 10620606006618 |
| 280-HP341SR-07 | 620606006642 | 10620606006649 |



| 280-HP341SR-08 | 620606006659 | 10620606006656 |
|----------------|--------------|----------------|
| 280-HP341SR-09 | 620606006666 | 10620606006663 |
| 280-HP341SR-11 | 620606006680 | 10620606006687 |
| 280-HP341SR-15 | 620606006710 | 10620606006717 |
| 280-HP341SR-17 | 620606006727 | 10620606006724 |
| 280-HP341SR-71 | 620606006758 | 10620606006755 |
| 280-HP341SR-74 | 620606006765 | 10620606006762 |

DIMENSIONS (in/cm)

| Α | 6.5/16.51 |
|---|------------|
| В | 12.0/30.48 |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSIY PROVIDED.