



PL3/O-6 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
PL3/O-2	2	1.60
PL3/O-3	3	2.38
PL3/O-4	4	3.16
PL3/O-5	5	3.94
PL3/O-6	6	4.72
PL3/O-8	8	6.28
PL3/O-10	10	7.84
PL3/O-12	12	9.40
PL3/O-14	14	10.96



WIRE ENTRY PORT
WIRE RANGE: 3/0 - #6 AWG
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSI FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- CONNECTOR CHROMATED FOR INCREASED CORROSION RESISTANCE.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.

		POLARIS SALES CO. INC	
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE: UNINSULATED 3/0 CONNECTOR	
NAME S.PARRY		DATE 07/2012	
DWG. NO. PL3,0-			
MATERIAL: N/A		SCALE: N/A	
		SHEET: 1 OF 1	