



IPL750-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL750-3	3	4.95
IPL750-4	4	6.38
IPL750-5	5	7.80
IPL750-6	6	9.23
IPL750-8	8	12.08
IPL750-10	10	14.93

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

1. CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
2. DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
3. COLD TEMPERATURE RATED TO -45°C.
4. HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		<b>POLARIS</b> SALES CO. INC
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		<b>TITLE:</b> INSULATED 750 CONNECTOR
DRAWN BY: S.PARRY		<b>DWG. NO.</b> IPL750-
DATE: 06/2012		SCALE: N/A
MATERIAL: N/A		SHEET: 1 OF 1