

EASY-SPLICE™

Direct Burial Roll-On Splice Sleeve

ROS SERIES



FEATURES

- Easy “roll-on” way to insulate and seal cable connections up to 1,000 volts.
- The gripping force of the EPDM elastomer combines with high performance sealant to form a water resistant, UV resistant insulating sleeve appropriate for direct burial application over in-line compression connectors.
- Ideal for use where gas or electric heating devices are not approved.
- RUS accepted for use as a secondary tap or splice cover.
- Each kit includes one Easy-Splice™ sleeve and sealant strips.

RATINGS



RATING:

Qualified to ANSI C119.1-1986. CSA certified to C22.2 No. 198.2. UL 486D listed, suitable for direct burial.

APPLICATION:

For use on standard poly or elastomeric-insulated cables. Insulates and seals in-line compression connectors or terminal lugs. Cable can be energized immediately.

All dimensional data is listed in inches.

CAT. NO.	WIRE RANGE	CABLE O.D.	SLEEVE LENGTH	MAX. CONNECTOR LENGTH	STD. CTN. QTY.
ROS-2/0	8-2/0 AWG	0.22-0.68	8.00	5.00	5
ROS-250	1/0 AWG-250 MCM	0.50-0.90	9.50	4.50	5
ROS-600	250-600 MCM	0.70-1.20	12.00	7.00	5

