

## CABLE TIES

# Air Handling and Push Mount Cable Ties

-P, -PM SERIES



## AIR HANDLING CABLE TIES



- Air handling ties are approved for indoor use in air handling spaces other than plenums and ducts per NFPA-1993.
- Meets UL 1565 test standards. MIL spec. 3367-1, -7, -2. NEC Sec. 300-22 (C) & (D), Rules 12-010 (3), (4), and (5) and 12-020 of the Canadian Electrical code, Part 1.
- Made of high strength nylon, these ties are self-extinguishing and resist abrasions and chemicals such as oil, greases, solvents, dilute acids and alkalis.
- Burgundy in color for easy identification.

### TEMPERATURE RATING:

Maximum operating temperature 85 °C (185 °F).

MAX. WIRE/ CABLE SIZE	CAT. NO.	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
7"	<b>750-P</b>	1.750	50 Lbs.	7.500	0.180	100	5,000
11"	<b>1150-P</b>	3.000	50 Lbs.	11.100	0.180	100	5,000
14"	<b>1450-P</b>	4.000	50 Lbs.	14.200	0.180	100	5,000

## PUSH MOUNT CABLE TIES



- Secure a cable tie to a back panel quickly and easily, eliminating the possibility of adhesive mount failure.
- Drill the mounting hole and insert.
- Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases, solvents, dilute acids and alkalines.
- Fungus-resistant, self-extinguishing and excellent dielectric properties.

### TEMPERATURE RATING:

-40 °C to 85 °C (-40 °F to 185 °F) and will withstand temperatures up to 149 °C (300.2 °F).  
94V-2 flammability rating.



MAX. WIRE/ CABLE SIZE	CAT. NO.	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	MTG. HOLE SIZE REQ. (IN.)	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
6"	<b>640-PM</b>	1.59	40 Lbs.	3/16	6.125	0.139	100	1,000