



S.P.S.T

Terminal Positions



CAT. NO.	CIRCUIT FUNCTIONS	POLES & THROWS	RATINGS			ACTUATOR STYLE	ACTUATOR MATERIAL	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	H.P 125-250VAC				
78280TS	ON-OFF	SPST	16*	8*	1	Bat	Brass/Nickel	Screws	5
78015TS	ON-OFF	SPST	20	10	—	Flat	Nylon	Screws	5
Dimensions (IN) A: 0.687 B: 0.280 C: 0.687 D: 0.375 E: 1.000 F: 0.588 KEYWAY: 0.072 X 0.038									



S.P.S.T

Terminal Positions

CAT. NO.	CIRCUIT FUNCTIONS	POLES & THROWS	RATINGS			ACTUATOR STYLE	ACTUATOR MATERIAL	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	H.P 125-250VAC				
78050TQ	ON-OFF	SPST	20	10	3/4	Bat	Brass/Nickel	0.250 Quikconnect	5
78130TS	ON-OFF	SPST	6	3	—	Ball	Brass/Nickel	Screws	5
78150TS	ON-OFF	SPST	20	10	3/4	Spade	Brass/Nickel	Screws	5
Dimensions (IN) A: 0.687 B: 0.465 C: 0.585 D: 0.522 E: 0.312 THREAD: 15/32-32UNS-2A KEYWAY: 0.072 X 0.038									



D.P.S.T

Terminal Positions

CAT. NO.	CIRCUIT FUNCTIONS	POLES & THROWS	RATINGS			ACTUATOR STYLE	ACTUATOR MATERIAL	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	H.P 125-250VAC				
78290TS	ON-OFF	DPST	16*	8*	1	Bat	Brass/Nickel	Screws	5
Dimensions (IN) A: 0.687 B: 0.465 C: 0.765 D: 0.836 E: 1.750 F: 1.764 THREAD: 15/32-32UNS-2A KEYWAY: 0.072 X 0.038									