

Metric Timing Pulleys



T Series - 5 mm Pitch Aluminum, Pilot Bore

Part No: 21T5/24-2

21 = Length thru Bore


T5 = Tooth Profile and Pitch

24 = Number of Teeth


2 = Number of Flanges



Models Available



Type 6



Type 6F

T-5 mm Pitch x 10 mm Belt Width

Dimensions in mm

Part No.	Part Code	Teeth	Type	Belt Width	Material	Dp	De	Df	Dm	F	L	d	Wt. kg
21T5/10-2	10T5-21	10	6F	10	AL	16.05	15.05	20.0	8	15	21	4	0.01
21T5/12-2	12T5-21	12	6F	10	AL	19.25	18.25	23.0	11	15	21	4	0.02
21T5/14-2	14T5-21	14	6F	10	AL	22.45	21.45	25.0	13	15	21	4	0.02
21T5/15-2	15T5-21	15	6F	10	AL	24.05	23.05	28.0	16	15	21	6	0.02
21T5/16-2	16T5-21	16	6F	10	AL	25.06	24.60	32.0	18	15	21	6	0.03
21T5/18-2	18T5-21	18	6F	10	AL	28.80	27.80	32.0	20	15	21	6	0.03
21T5/19-2	19T5-21	19	6F	10	AL	30.40	29.40	36.0	22	15	21	6	0.04
21T5/20-2	20T5-21	20	6F	10	AL	32.00	31.00	36.0	23	15	21	6	0.04
21T5/22-2	22T5-21	22	6F	10	AL	35.15	34.15	38.0	24	15	21	6	0.05
21T5/24-2	24T5-21	24	6F	10	AL	38.40	37.40	42.0	26	15	21	6	0.05
21T5/25-2	25T5-21	25	6F	10	AL	39.95	38.95	44.0	26	15	21	6	0.09
21T5/26-2	26T5-21	26	6F	10	AL	41.60	40.60	44.0	26	15	21	6	0.06
21T5/27-2	27T5-21	27	6F	10	AL	43.20	42.20	48.0	30	15	21	8	0.06
21T5/28-2	28T5-21	28	6F	10	AL	44.75	43.75	48.0	32	15	21	8	0.07
21T5/30-2	30T5-21	30	6F	10	AL	47.95	46.95	51.0	34	15	21	8	0.08
21T5/32-2	32T5-21	32	6F	10	AL	51.10	50.10	54.0	38	15	21	8	0.09
21T5/36-2	36T5-21	36	6F	10	AL	57.45	56.45	63.0	38	15	21	8	0.11
21T5/40-2	40T5-21	40	6F	10	AL	63.85	62.85	66.0	40	15	21	8	0.14
21T5/42-2	42T5-21	42	6F	10	AL	67.00	66.00	71.0	40	15	21	8	0.18
21T5/44-0	44T5-21	44	6	10	AL	70.20	69.20	—	45	15	21	8	0.19
21T5/48-0	48T5-21	48	6	10	AL	76.55	75.55	—	50	15	21	8	0.20
21T5/60-0	60T5-21	60	6	10	AL	95.65	94.65	—	65	15	21	8	0.31

T-5 mm Pitch x 16 mm Belt Width

Part No.	Part Code	Teeth	Type	Belt Width	Material	Dp	De	Df	Dm	F	L	d	Wt. kg
27T5/10-2	10T5-27	10	6F	16	AL	16.05	15.05	20.0	8	21	27	4	0.016
27T5/12-2	10T5-27	12	6F	16	AL	19.25	18.25	23.0	11	21	27	4	0.022
27T5/14-2	14T5-27	14	6F	16	AL	22.45	21.45	25.0	13	21	27	4	0.026
27T5/15-2	15T5-27	15	6F	16	AL	24.05	23.05	28.0	16	21	27	6	0.029
27T5/16-2	16T5-27	16	6F	16	AL	25.06	24.60	32.0	18	21	27	6	0.035
27T5/18-2	18T5-27	18	6F	16	AL	28.80	27.80	32.0	20	21	27	6	0.043
27T5/19-2	19T5-27	19	6F	16	AL	30.40	29.40	36.0	22	21	27	6	0.049
27T5/20-2	20T5-27	20	6F	16	AL	32.00	31.00	36.0	23	21	27	6	0.053
27T5/22-2	22T5-27	22	6F	16	AL	35.15	34.15	38.0	24	21	27	6	0.054
27T5/24-2	24T5-27	24	6F	16	AL	38.40	37.40	42.0	26	21	27	6	0.076
27T5/25-2	25T5-27	25	6F	16	AL	39.95	38.95	44.0	26	21	27	6	0.081
27T5/26-2	26T5-27	26	6F	16	AL	41.60	40.60	44.0	26	21	27	6	0.085
27T5/27-2	27T5-27	27	6F	16	AL	43.20	42.20	48.0	30	21	27	8	0.090
27T5/28-2	28T5-27	28	6F	16	AL	44.75	43.75	48.0	32	21	27	8	0.092
27T5/30-2	30T5-27	30	6F	16	AL	47.95	46.95	51.0	34	21	27	8	0.105
27T5/32-2	32T5-27	32	6F	16	AL	51.10	50.10	54.0	38	21	27	8	0.123
27T5/36-2	36T5-27	36	6F	16	AL	57.45	56.45	63.0	38	21	27	8	0.160
27T5/40-2	40T5-27	40	6F	16	AL	63.85	62.85	66.0	40	21	27	8	0.193
27T5/42-2	42T5-27	42	6F	16	AL	67.00	66.00	71.0	40	21	27	8	0.205
27T5/44-0	44T5-27	44	6	16	AL	70.20	69.20	—	45	21	27	8	0.228
27T5/48-0	48T5-27	48	6	16	AL	76.55	75.55	—	50	21	27	8	0.280
27T5/60-0	60T5-27	60	6	16	AL	95.65	94.65	—	65	21	27	8	0.430

Note: Finished Bore & Keyway available on request.