


PANEL CHANNEL

Solid Wall Panel Channel, Floor Duct

PC, FD SERIES



SOLID WALL PANEL CHANNEL



- Made from high-impact, self-extinguishing, warp-proof PVC for routing wires where wire extraction is not necessary.
- Supplied complete with mounting holes and non-slip, snap-on and off covers.
- Optional adhesive backing is available.
- Maximum service temperature: 85 °C (185 °F).
- Tested to UL File up to 50 °C (122 °F). 94V-0 Rated.
- For other sizes, please contact NSI.

CAT. NO.	COLOR	NOMINAL SIZE (IN)	LENGTH (FT.)	STD. PKG. QTY.	STD. CTN. QTY.
PC2020	Grey	2 x 2	6'	6'	72'
PC2030	Grey	2 x 3	6'	6'	72'
PC3030	Grey	3 x 3	6'	6'	72'
PC4040	Grey	4 x 4	6'	6'	72'

FLOOR DUCT

- 2.5" and 4" wide floor duct for use as safe temporary enclosure of electrical cords, data communications cables and other objects that present a trip hazard.
- Manufactured using soft PVC.



CAT. NO.	NOMINAL SIZE (IN.)	COLOR	LENGTH (FT.)	WIDTH (IN)		HEIGHT (IN)		STD. PKG. QTY.	STD. CTN. QTY.
				ID	OD	ID	OD		
FD250W	2.5"	Off White	6'	0.750	2.600	0.430	0.600	6'	18'
FD250B		Brown	6'	0.750	2.600	0.430	0.600	6'	18'
FD250K		Black	6'	0.750	2.600	0.430	0.600	6'	18'
FD400W	4"	Off White	6'	1.160	4.000	0.610	0.910	6'	18'
FD400B		Brown	6'	1.160	4.000	0.610	0.910	6'	18'
FD400K		Black	6'	1.160	4.000	0.610	0.910	6'	18'