

EASY-SPLICE™

Heavy Wall Heat Shrink For Direct Burial And Submersible HWHS SERIES



FEATURES

- Made of specially formulated polyolefin irradiated and thermally stabilized to give the material "elastic memory"
- When a proper amount of heat is directly applied to the shrink sleeve, it will permanently shrink to its original unexpanded diameter tightly cover and "mold" itself into irregular shapes
- The interior of the sleeve is coated with an adhesive that assures a watertight seal after shrinking
- For use on standard poly- or elastomeric-insulated/jacketed cables or lead-jacketed cables, which may include aluminum or steel armoring.
- RUS accepted for use as a secondary tap or splice cover. May be used for jacket repair on cables up to 35 kV
- Heavy wall heat shrink is also available without sealant. Medium wall heat shrink and flame retardant heavy wall heat shrink also available, with or without sealant (not UL Listed)

RATINGS



UL 486D Listed
CSA C22.2

TEMPERATURE RATING:

121-135 °C, 1000V.

APPLICATION:

Qualified to ANSI C119.1-1986 for underground splicing. Insulate and seal buried electrical connections rated up to 1,000 volts.

CONNECTORS UP TO 6 INCHES:

Recommended cut length = Connector length + 4 inches.

CONNECTORS OVER 6 INCHES:

Recommended cut length = Connector length + 5 inches.

All dimensional data is listed in inches.

CAT. NO.	SEALABLE WIRE RANGE
HWHS14-6-6	14-6 AWG
HWHS14-6-12	14-6 AWG
HWHS14-6-48	14-6 AWG
HWHS8-2-6	8-2 AWG
HWHS8-2-12	8-2 AWG
HWHS8-2-48	8-2 AWG
HWHS6-40-4	6-4/0 AWG
HWHS6-40-6	6-4/0 AWG
HWHS6-40-9	6-4/0 AWG
HWHS6-40-12	6-4/0 AWG
HWHS6-40-48	6-4/0 AWG
HWHS2-500-4	2 AWG - 500 MCM
HWHS2-500-6	2 AWG - 500 MCM
HWHS2-500-8	2 AWG - 500 MCM
HWHS2-500-9	2 AWG - 500 MCM
HWHS2-500-12	2 AWG - 500 MCM
HWHS2-500-48	2 AWG - 500 MCM
HWHS20-750-6	2/0 AWG - 750 MCM
HWHS20-750-9	2/0 AWG - 750 MCM
HWHS20-750-12	2/0 AWG - 750 MCM
HWHS20-750-48	2/0 AWG - 750 MCM
HWHS250-1000-6	250-1000 MCM
HWHS250-1000-9	250-1000 MCM
HWHS250-1000-12	250-1000 MCM
HWHS250-1000-48	250-1000 MCM
HWHS500-1500-9	500-1500 MCM
HWHS500-1500-12	500-1500 MCM
HWHS500-1500-48	500-1500 MCM
HWHS800-2000-12	800-2000 MCM
HWHS800-2000-48	800-2000 MCM
HWHS1500-2500-12	1500-2500 MCM
HWHS1500-2500-48	1500-2500 MCM



LENGTH	GENERAL USE RANGE		MAX. CONNECTOR O.D.	MIN. SEAL LENGTH PER SIDE	STD. PKG. QTY.
	RECOVERED	EXPANDED			
6	0.130	0.390	0.290	1.500	3
12	0.130	0.390	0.290	1.500	3
48	0.130	0.390	0.290	1.500	3
6	0.170	0.550	0.410	2.000	3
12	0.170	0.550	0.410	2.000	3
48	0.170	0.550	0.410	2.000	3
4	0.250	0.860	0.690	2.000	3
6	0.250	0.860	0.690	2.000	3
9	0.250	0.860	0.690	2.000	3
12	0.250	0.860	0.690	2.000	3
48	0.250	0.860	0.690	2.000	3
4	0.350	1.220	1.060	2.000	3
6	0.350	1.220	1.060	2.000	3
8	0.350	1.220	1.060	2.000	3
9	0.350	1.220	1.060	2.000	3
12	0.350	1.220	1.060	2.000	3
48	0.350	1.220	1.060	2.000	3
6	0.510	1.730	1.300	2.000	3
9	0.510	1.730	1.300	2.000	3
12	0.510	1.730	1.300	2.000	3
48	0.510	1.730	1.300	2.000	3
6	0.700	1.960	1.500	2.000	3
9	0.700	1.960	1.500	2.000	3
12	0.700	1.960	1.500	2.000	3
48	0.700	1.960	1.500	2.000	3
9	0.860	2.480	1.840	2.500	3
12	0.860	2.480	1.840	2.500	3
48	0.860	2.480	1.840	2.500	3
12	1.290	3.930	-	2.500	3
48	1.290	3.930	-	2.500	3
12	1.490	4.640	-	2.500	3
48	1.490	4.640	-	2.500	3