

CABLE TIES

Cable Ties with Stainless Steel Barb

-SB SERIES



FEATURES

- Natural and UV resistant black, nylon cable ties have stainless steel barb; barb is at 45° pitch with 60° cutting angle, setting strap to desired position to suit all diameters in range.
- Flexible and resistant at low temperatures and humidity-free environments.
- Cold and fastening resistances are higher than normal cable tie tolerances.

RATINGS



TEMPERATURE RATINGS:

Min., -40°F to Max., 185°F (-40°C to 85°C)

IDEAL STORAGE:

23°C, Humidity 50%, Avoid storing cable ties next to warm objects

TYPE 21 AH-1:

"Suitable for use in air-handling spaces (Plenums)"

MAX. WIRE/ CABLE SIZE	CAT. NO.
4"	418-SB
5"	540-SB
7"	750-SB
8"	818-SB
	840-SB
	1140-SB
11"	1150-SB
	1450-SB
14"	14120-SB
4"	4180-SB
5"	5400-SB
7"	7500-SB
8"	8180-SB
	8400-SB
	11400-SB
11"	11500-SB
	14500-SB
14"	141200-SB



COLOR	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.
Natural	0.944	18 Lbs.	4.000	0.100	100
Natural	1.417	40 Lbs.	5.500	0.137	100
Natural	2.007	50 Lbs.	7.322	0.177	100
Natural	2.165	18 Lbs.	7.874	0.100	100
Natural	2.165	40 Lbs.	7.874	0.137	100
Natural	3.149	40 Lbs.	11.023	0.137	100
Natural	3.149	50 Lbs.	11.023	0.177	100
Natural	3.976	50 Lbs.	14.173	0.177	100
Natural	3.976	120 Lbs.	14.173	0.295	50
UV Black	0.944	18 Lbs.	4.000	0.100	100
UV Black	1.417	40 Lbs.	5.500	0.137	100
UV Black	2.007	50 Lbs.	7.322	0.177	100
UV Black	2.165	18 Lbs.	7.874	0.100	100
UV Black	2.165	40 Lbs.	7.874	0.137	100
UV Black	3.149	40 Lbs.	11.023	0.137	100
UV Black	3.149	50 Lbs.	11.023	0.177	100
UV Black	3.976	50 Lbs.	14.173	0.177	100
UV Black	3.976	120 Lbs.	14.173	0.295	50