



Pipe Thread Seal Tape - PTFE

- Seals and makes joints leaktight regardless of pipe material or fluid. Just a quick wind around male joint. This pure PTFE tape resists temperatures from -450° to +500° F. Ideal for steam lines, heating, cooling and cryogenic systems, oil refinery pipes, aircraft fittings and missile systems. Averages less than a cent per application, eliminates liquids, pastes and brushes.
- **THE VERSATILE SEALANT**
PASCO PTFE tape will seal all threaded joints-any material: copper, brass, cast iron, aluminum, monel, stainless steel, plastic, synthetic rubber, glass, or ceramic. In addition to resisting high and low temperatures, it can be used for high pressure or vacuum-liquid or gas.
- **KEEPS THREADS INTACT**
 Self lubricating **PASCO** PTFE tape makes assembly or disassembly easy. Eliminates the need for over tightening. Prevents galling, seizing and cross threading.
- **MINIMUM MAINTENANCE**
 PTFE tape remains impervious to the most corrosive fluids for the life of the joint. Won't dry out, crack, melt, or dissolve. Stands up to maximum pressures and vibration.
- **MEETS MIL SPEC T-27730A**



| WIDTH | 260" | 520" | 1296" |
|-------|----------|----------|---------|
| 1/2" | 9010-25 | 9014-25 | 9018-10 |
| 1/2" | 9010-100 | 9014-100 | 9018-50 |
| 3/4" | 9020-25 | — | — |
| 3/4" | 9020-70 | — | — |
| 1" | 9030-50 | 9034-50 | — |

Yellow Gas Line Thread Seal Tape - PTFE

- Specifically designed to seal threads in natural gas, propane, butane, kerosene and petroleum oil lines.
- **MEETS MIL SPEC T-27730A**
- For use on threads NOT exceeding 1-1/2"



| PART NUMBER | WIDTH x LENGTH |
|-------------|----------------|
| 9000-100 | 1/2" x 260' |