

CABLE TIES

Cable Ties with Stainless Steel Barb

-SB Series

FEATURES

- Natural and UV resistant black, nylon cable ties have stainless steel barb; barb is at 45° pitch with 60° cutting angle, setting strap to desired position to suit all diameters in range.
- Flexible and resistant at low temperatures and humidity-free environments.
- Cold and fastening resistances are higher than normal cable tie tolerances.

SPECIFICATIONS

- cULus Listed for Positioning Devices UL62275.
- **Temperature Rating:** Min., -40°F to Max., 185°F (-40°C to 85°C).
- **Ideal Storage:** 23°C, Humidity 50%, Avoid storing cable ties next to warm objects.
- **Type 21 AH-2:** "Suitable for use in air-handling spaces (Plenums)".



CAT. NO.	COLOR	MAX. WIRE/CABLE SIZE	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.
418-SB	Natural	4"	0.944	18 Lbs.	4.000	0.100	100
540-SB	Natural	5"	1.417	40 Lbs.	5.500	0.137	100
750-SB	Natural	7"	2.007	50 Lbs.	7.322	0.177	100
818-SB	Natural	8"	2.165	18 Lbs.	7.874	0.100	100
840-SB	Natural	8"	2.165	40 Lbs.	7.874	0.137	100
1140-SB	Natural	11"	3.149	40 Lbs.	11.023	0.137	100
1150-SB	Natural	11"	3.149	50 Lbs.	11.023	0.177	100
1450-SB	Natural	14"	3.976	50 Lbs.	14.173	0.177	100
14120-SB	Natural	14"	3.976	120 Lbs.	14.173	0.295	50
4180-SB	UV Black	4"	0.944	18 Lbs.	4.000	0.100	100
5400-SB	UV Black	5"	1.417	40 Lbs.	5.500	0.137	100
7500-SB	UV Black	7"	2.007	50 Lbs.	7.322	0.177	100
8180-SB	UV Black	8"	2.165	18 Lbs.	7.874	0.100	100
8400-SB	UV Black	8"	2.165	40 Lbs.	7.874	0.137	100
11400-SB	UV Black	11"	3.149	40 Lbs.	11.023	0.137	100
11500-SB	UV Black	11"	3.149	50 Lbs.	11.023	0.177	100
14500-SB	UV Black	14"	3.976	50 Lbs.	14.173	0.177	100
141200-SB	UV Black	14"	3.976	120 Lbs.	14.173	0.295	50