

# SPECIFICATION SHEET 56-3175



# THINLY COATED NITRILE

- Armor<sup>™</sup> Series gloves feature a unique combination of low-coating deposit weight and high abrasion resistance and provide the wear of heavier, bulkier nitrile coated gloves without sacrificing flexibility and tactile sensitivity
- Comfortable and flexible, provides excellent dexterity
  Thinly coated with blue nitrile on cotton interlock liner
- Textured coating provides a great grip
- ActiFresh<sup>™</sup> treated to reduce germs and odors

## APPLICATIONS

Used for general handling, assembly, fabrication, parts handling, inspection, maintenance and shipping and receiving.

# **CARE INSTRUCTIONS**

Use commercial detergents or laundry soap. Wash in warm to medium hot water temperature no more than 30°C (90°F) for a maximum of 10 minutes. Rinse in cold water. Tumble dry at a 60°C (140°F). For best results, turn gloves inside out while drying. Do not use solvents or dry clean.

## **TECHNICAL DATA**

| MATERIAL    | Nitrile, Cotton         |  |                   |  |
|-------------|-------------------------|--|-------------------|--|
| COLOR       | Blue/White              | 🗆 Blue/White                               |                   |  |
| CUFF STYLE  | Plasticized safety cuff |  |                   |  |
| SIZES       | M - XL                  | M - XL                                     |                   |  |
| PACKAGING   | 12 pair per dozen; 6    | 12 pair per dozen; 6 dozen per case        |                   |  |
| CASE        | 11.8" x 10.6" x 13.8"   | 11.8" x 10.6" x 13.8" / 30cm x 27cm x 35cm |                   |  |
| CASE WEIGHT | M                       | L  | XL                |  |
|             | 15.0 bs / 6.8 kg        | 16.2 lbs / 7.3 kg                          | 17.7 lbs / 8.0 kg |  |
| C00         | Sri Lank                |  |                   |  |

# PERFORMANCE PROPERTIES

#### EN388: 4121

| ABRASION | 0 | 1 | 2 | 3 | 4 | 5 |
|----------|---|---|---|---|---|---|
| CUT      | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR     | 0 | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | 5 |

## BARCODES


| ITEM        | BAG | DOZEN          | CASE           |
|-------------|-----|----------------|----------------|
| 🗖 56-3175/M |     | 01616314006258 | 02616314006258 |
| 🗖 56-3175/L |     | 01616314006265 | 02616314006265 |
| 56-3175/XL  |     | 01616314006272 | 02616314006272 |



## **DIMENSIONS** (in/cm)

|   | М           |             | XL          |
|---|-------------|-------------|-------------|
| Α | 10.6 / 27.0 | 10.8 / 27.5 | 11.0 / 28.0 |
| В | 4.5 / 11.5  | 5.1 / 13.0  | 5.2 / 13.2  |
|   |             |             |             |

### Thickness - palm: 0.9 (+/-.01) mm



#### PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.