



Take care of plumbing system repairs or remodeling projects fast with a variety of NIBCO® Wrot Racer™ patented premium copper push fittings that you simply push into place until they lock. Top-flight delivery rates ensure you'll have NIBCO product available when you need it, saving you time so you can race ahead to your next project.

PREMIUM COPPER PUSH FITTINGS

FITTINGS

APPLICATIONS

- Specifically Designed for Use in Commercial and Residential Potable Water Systems
- For Use With: Hard-drawn Copper K, L, and M; PEX or PE-RT (with tube stiffeners); CPVC-CTS
- Removal Tool Easily Disconnects Any Joint

MATERIALS & CONSTRUCTION

- 99.9% Pure Wrot Copper Body
- PPSU Engineered Plastic
- Stainless Steel Gripper Ring
- Manufactured From Recyclable Materials

DESIGN CRITERIA

- Certified to 200 PSI and 200° F
- Fittings Meet NSF/ANSI 14, 61 and 372 and ASSE 1061



Push fittings install quickly and easily for a secure connection.



Create a simple and secure connection without any soldering, crimping or joining materials.



Manufactured in the USA from 99.9% globally-sourced pure wrot copper.

AHEAD OF THE FLOW®


NIBCO INC.
WORLD HEADQUARTERS
WEB: www.nibco.com

1516 MIDDLEBURY STREET
ELKHART, IN 46516-4740
USA

DOMESTIC CUSTOMER SERVICE
PHONE: 800.234.0227
FAX: 800.234.0557


INTERNATIONAL OFFICE
PHONE: +1/574.295.3327
FAX: +1/574.295.3455

ADAPTERS



P603
Adapter - Push x Female


NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES			
		A	H	L	W
1/2	0.10	$\frac{27}{32}$	$1\frac{1}{16}$	$1\frac{11}{16}$	1
3/4	0.16	$\frac{29}{32}$	$1\frac{5}{16}$	$1\frac{7}{8}$	$1\frac{9}{32}$



P604
Adapter - Push x Male

NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES			
		B	H	L	W
1/2	0.08	$\frac{11}{16}$	1	$1\frac{17}{32}$	1
3/4	0.14	$\frac{25}{32}$	$1\frac{9}{32}$	$1\frac{3}{4}$	$1\frac{9}{32}$


CAPS



P617
Cap - Push

NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES			
		H	L	N	W
1/2	0.03	1	$\frac{29}{32}$	$\frac{1}{32}$	1
3/4	0.05	$\frac{19}{32}$	$1\frac{1}{32}$	$\frac{1}{32}$	$1\frac{9}{32}$
1	0.08	$1\frac{19}{32}$	$1\frac{3}{16}$	$\frac{1}{32}$	$1\frac{19}{32}$


COUPLINGS



P600
Coupling - Push x Push

NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES			
		A	H	L	W
1/2	0.05	$\frac{1}{32}$	1	$1\frac{3}{4}$	1
3/4	0.09	$\frac{1}{32}$	$1\frac{9}{32}$	2	$1\frac{9}{32}$
1	0.14	$\frac{1}{32}$	$1\frac{19}{32}$	$2\frac{1}{4}$	$1\frac{19}{32}$


ELBOWS



P607
90° Elbow - Push x Push

NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES				
		C	D	H	L	W
1/2	0.07	$\frac{13}{32}$	$\frac{13}{32}$	$1\frac{7}{8}$	$1\frac{7}{8}$	1
3/4	0.13	$\frac{1}{2}$	$\frac{1}{2}$	$2\frac{7}{32}$	$2\frac{7}{32}$	$1\frac{9}{32}$
1	0.21	$\frac{21}{32}$	$\frac{21}{32}$	$2\frac{9}{16}$	$2\frac{9}{16}$	$1\frac{19}{32}$


TEES



P611
Tee - Push x Push x Push

NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES					
		C	F	G	H	L	W
1/2	.11	$\frac{11}{32}$	$\frac{11}{32}$	$\frac{13}{32}$	$1\frac{27}{32}$	$2\frac{19}{32}$	1
3/4	.23	$\frac{5}{8}$	$\frac{5}{8}$	$\frac{11}{16}$	$2\frac{5}{16}$	$3\frac{7}{32}$	$1\frac{9}{32}$
1	.36	$\frac{11}{16}$	$\frac{11}{16}$	$\frac{21}{32}$	$2\frac{9}{16}$	$3\frac{19}{32}$	$1\frac{19}{32}$

Visit our website for the most current information.



Lead-Free* Push Fittings - MATERIAL LIST

PART	SPECIFICATION
1. Release Collar	PPSU
2. Upper Cartridge	PPSU
3. Grip Ring	316SS
4. Lower Cartridge	PPSU
5. Seal	EPDM
6. Body	Wrot Copper

ACCESSORIES



Removal Tool

NOM. SIZE	APPROX. NET WT./LBS.
1/4	0.013
3/8	0.013
1/2	0.013
3/4	0.013
1	0.013


INSTALLATION INSTRUCTIONS

Before installing, turn water off at main shut-off valve.


Antes de la instalación, cierre el flujo de agua en la válvula principal.

Removable & Reusable
Extraíble y reutilizable


Installation/Instalación




1. Cut tube
Corte el tubo



2. Prepare tube
(remove all sharp edges & burrs)
Prepare el tubo
(quitetodos los bordes afilados las rebabas)




3. Mark insertion depth
Marque la profundidad de inserción



4. Push fitting on tube to the mark
(use tube stiffeners with PEX only)
Empuje la conexión en el tubo hasta la marca
(utilice refuerzos de tubos con PEX solamente)

Removal/Extracción



Push the disconnect clip against the release collar and pull the pipe with a twisting action.
Empuje el clip de desconexión contra el collar de liberación, y extraiga el tubo con un movimiento giratorio.

Insert Depth Chart/ Gráfico de inserción de profundidad

Fitting Size <i>Tamaño de conexión</i>	1/2"	3/4"	1"
Insert Depth - in. <i>Profundidad de inserción</i>	7/8"	1"	1-1/8"
Insert Depth - cm. <i>Profundidad de inserción</i>	2.22	2.54	2.85



Made in the USA from recyclable materials.
Hecho en los EE. UU. Con materiales reciclables.

Patent 10,006,575

Visit our website for the most current information.

NIBCO® Wrot Racer™ Fittings Warranty

NIBCO INC. LIMITED WARRANTY

Applicable to NIBCO INC. Wrot Racer Premium Copper Push-to-Connect Fittings

NIBCO INC. warrants:

- NIBCO Wrot Racer fittings to be free from defects in materials and workmanship under normal use and service, for a period of twenty five (25) years from the date of original installation.

In the event any defect in material or workmanship occurs which the owner believes is covered by this warranty, the owner should immediately contact NIBCO Technical Services, either in writing or by telephone at (888) 446-4226 or (574) 295-3000. The owner will be instructed to return the said product, at the owner's expense, to NIBCO INC., or to an authorized representative for inspection. In the event said inspection disclosed to the satisfaction of NIBCO INC. that said fitting connector is defective in material or workmanship, a replacement fitting will be shipped free of charge to the purchaser. This warranty is limited to the cost of repairing or replacing the product.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, THIS WARRANTY SPECIFICALLY EXCLUDES INCIDENTAL AND CONSEQUENTIAL DAMAGES OF EVERY TYPE AND DESCRIPTION RESULTING FROM ANY CLAIMED DEFECT IN MATERIAL OR WORKMANSHIP, INCLUDING BUT NOT LIMITED TO, PERSONAL INJURIES AND PROPERTY MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFIC EXCLUDED.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state and country to country.



How to Order

State quantity, figure number and size for each valve or fitting you wish to order. See individual catalog pages for specific or special product designations.

HOW MANY TO ORDER

NIBCO® fittings are decimal packed for your convenience in handling, shipping and stock-keeping. Number in master carton varies with item.

POLICY ON RETURNS TO FACTORY

No NIBCO fittings are to be returned without prior written agreement. Transportation must be prepaid. There is a 20% standard restocking fee to cover cost of rehandling and reinspection. There is a 30% restocking fee for Assemble-To-Order items.

TECHNICAL ASSISTANCE

Engineers, contractors, wholesalers or manufacturers may obtain special or technical assistance from any factory representative of NIBCO.

NIBCO INC.
World Headquarters
1516 Middlebury Street
Elkhart, IN 46516-4740
USA

PH: 1.574.295.3000 or 1.888.446.4226
FAX: 1.574.295.3307 or 1.888.336.4226
EMAIL: CS-TechnicalServices@nibco.com

To the best of our knowledge, the information contained in this publication is accurate. However, NIBCO does not assume any liability whatsoever for the accuracy or completeness of such information. Final determinations of the suitability of any information or product for the use to be contemplated is the sole responsibility of the user. The manner of that use, and whether there is any infringement of patents, is also the sole responsibility of the user.