



8-WAY™

COMPLETE BOILER WATER TREATMENT

DESCRIPTION

8-WAY™ is a complete boiler water treatment for steam and hot water systems. **8-WAY™**: 1) Removes sludge. 2) Removes rust scale. 3) Inhibits boiler corrosion. 4) Inhibits steam line corrosion. 5) Prevents oxygen pitting. 6) Inhibits lime scale. 7) Prevents surging and foaming. 8) Controls pH with color indicator.

CHARACTERISTICS

* Nonchromate - Biodegradable

* Contains no petroleum distillates

* Will not harm seals or gaskets

* Color coded cure

APPLICATIONS

8-WAY™ can be used for cleaning very dirty steam boilers. Boilers with excessive scale, rust and muck.

8-WAY™ can be used to maintain clean, rust free water on new or existing systems.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68712	Quart	12	31	0.71
68714	Gallon	4	42	1.27
68716	30 Gallon	1	296	N/A

8-WAY™ COMPLETE BOILER WATER TREATMENT

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

FOR CLEANING VERY DIRTY STEAM BOILERS WITH EXCESSIVE SCALE, RUST AND MUCK.

- Pour or pump 8-WAY™ into the boiler. Add enough to turn water violet. One quart is usually sufficient to treat a boiler with up to 30 gallons water content. (Approximately 600 square feet of radiation, or 5 (B.H.P.)
- Allow to steam for ½ to 3 hours, then drain and flush.
- Refill boiler with water and add one quart 8-WAY™ for each quart originally used. Leave 8-WAY™ in system to act as a rust inhibitor and water conditioner.

FOR MAINTAINING CLEAN, RUST FREE WATER AND FOR NEW INSTALLATIONS:

- Add one quart of 8-WAY™ for each 30 gallons of water content.
- Add more if necessary to turn water blue or violet.
- Leave in system to condition water for a full season.

FOR HOT WATER SYSTEMS:

- Use 1 quart for each 25 gallons of circulating water. Stops corrosion and scale.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

DANGER  **POISON!**
MAY BE FATAL IF SWALLOWED
CAUSES SKIN AND EYE BURNS
KEEP OUT OF REACH OF CHILDREN

CONTAINS SODIUM NITRITE AND CAUSTIC SODA. CORROSIVE: Do not get in eyes or on clothing. Wear protective clothing, safety goggles and rubber gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

FIRST AID: Skin: Flush with water for 15 minutes. Eyes: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Call physician immediately. Ingestion: Call a doctor or get medical attention. **DO NOT** induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	9.08
Flash Point SETA CC	None
Color	Dark blue or purple liquid
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com