

**TECHNICAL DATA****KRK-10****KRUD KUTTER®
WASTE PAINT AND COLORANT HARDENER****DESCRIPTION AND USES**

Krud Kutter® Waste Paint and Colorant Hardener is designed to turn liquid paint into a solid material for curbside disposal. It is easy to use and works in minutes. It is suitable for latex and oil-based paints and colorants.

A 3.5 oz. bag will treat 2/3 gallon of paint. A 5 gallon pail will treat 100 gallons of paint.

PRODUCTS

SKU	Description
PH3512	3.5 oz. Bag
PH1101	5-Gallon Pail

PRODUCT APPLICATION**DIRECTIONS**

Add the crystals to the waste or spilled latex paint or colorant. One cup of water may be added to thick paint for ease of use. Stir paint until thick. Scrape spills into a pile. Dispose of as regular garbage in accordance with local regulations. Can be used on oil-based paint spills, where the absorption rate of hardener is reduced.

CAUTION: AVOID CONTACT WITH SKIN AND EYES. Wash hands thoroughly after handling. For eye contact, flush with large quantities of water. Do not ingest. Avoid handling product dust.

KEEP OUT OF REACH OF CHILDREN.

PHYSICAL PROPERTIES

Physical Properties	WASTE PAINT AND COPLORANT HARDENER
Composition	Poly-Absorbant
Color	Clear
pH	NA
Volatile Organic Compounds	0% by weight
Practical Coverage	3.5 ounces – Treats 2/3 gallon
	5-Gallon – Treats 100 gallons
Shelf Life	NA
Flash Point	>200°F (93°C)
Caution!	CAUTION: AVOID CONTACT WITH SKIN AND EYES. Wash hands thoroughly after handling. For eye contact, flush with large quantities of water. Do not ingest. Avoid handling product dust. KEEP OUT OF REACH OF CHILDREN.
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.