



FABRICATED (APPEARANCE MAY VARY)

ASTM D2665, F1866, CSA B181.2 WHERE APPLICABLE

**1/32 BEND (11.25) HxH
PVC SOLVENT WELD DWV**

PART NO.	SIZE IN INCHES	L1	L2	H1	T	W	D1
D1934	4	3/4	3/4	2 1/4	6 7/16	5 9/16	5 1/32
D1936	6	1	1	3 1/4	9 1/8	8	7 7/32
D1938	8	1 1/4	1 1/4	4 1/4	11 13/16	10 11/32	9 11/32
D19310	10	1 3/8	1 3/8	5 3/8	14 1/2	12 23/32	11 17/32
D19312	12	1 1/2	1 1/2	6 3/8	16 15/16	15	13 19/32

-- DIMENSIONS AND APPEARANCE ARE APPROXIMATE AND SUBJECT TO CHANGE WITHOUT NOTICE DUE TO DESIGN OR PRODUCTION MODIFICATIONS
 -- MOLDED FITTING TOLERANCE = ±1/8" OVERALL LENGTH
 -- FABRICATED FITTING TOLERANCE = ±1" LINEAR, ± 2° ANGULAR

* MOLDED FITTING
 † ASSEMBLED FROM MOLDED COMPONENTS
 ALL OTHER FITTINGS ARE FABRICATED