

Long Hose Lengths | Series 30000

Hose I.D.	1/4"	3/8"	1/2"	3/4"	1"
	(6.4 mm)	(9.5 mm)	(12.7 mm)	(19.1 mm)	(25.4 mm)
Hose O.D.	.530"	.710"	.850"	1.188"	1.375"
	(13 mm)	(18 mm)	(22 mm)	(30 mm)	(35.0 mm)
"F" Width	Hose Capacity				
6"	200'	140'	100'	50'	N/A
(152 mm)	(61 m)	(43 m)	(30 m)	(15 m)	
12"	425'	300'	200'	100'	50'
(305 mm)	(130 m)	(91 m)	(61 m)	(30 m)	(15 m)
18"	625'	450'	325'	175'	100'
(457 mm)	(191 m)	(137 m)	(99 m)	(54 m)	(31 m)
22"	780'	550'	400'	225'	125'
(559 mm)	(238 m)	(168 m)	(122 m)	(69 m)	(38 m)
27"	1000'	700'	500'	275'	150'
(686 mm)	(305 m)	(213 m)	(152 m)	(84 m)	(46 m)

E	A	3	2	1	06	L	12D	X
Drive Type A - Air motor B - Bevel crank C - Hand crank E - Electric motor H - Hydraulic motor		Width of Spool See "F" Dimension 06 - 6" (152 mm) 12 - 12" (305 mm) 18 - 18" (457 mm) 22 - 22" (559 mm) 28 - 27" (686 mm)			Motor Type Blank X - Explosion proof electric motor			
Fluid Path Type A - Gooseneck B - No gooseneck (1" only) H - Heavy duty gooseneck (1" only)		Swivel Size 0 - No swivel 2 - 1/2" (13 mm) I.D. 3 - 3/4" (19 mm) I.D. 4 - 1/2" (13 mm) Dual 5 - 3/4" (19 mm) Dual 6 - 1/4" (6 mm) Dual 7 - 1" (25 mm) I.D. 8 - 1/2" (13 mm) I.D. pressure wash			Power Source Blank 12D - 12 V DC 24D - 24 V DC 10A - 115 V AC 4A - 1 1/2 HP air motor 6A - 4 HP air motor			
NOTE: This chart is for reference purposes only. Please see selection chart or consult manufacturer for additional models not listed or for any questions about option combinations.								
						Pressure L - 1000 PSI (69 bar) M - 3000 PSI (207 bar)		

Model without hose	Shipping Weight	Hose I.D.	Hose O.D.	Capacity	Pressure	NPT(F) Reel Outlet	NPT(F) Reel Inlet	D	E	F
	lbs kg	in mm	in mm	ft m	psi bar	in	in	in mm	in mm	in mm
Hand Crank Hose Reels Maximum temperature 210 °F (99 °C)										
CA32106 L	40 18	1/2 13	.750 19	100 30	1000 69	1/2	1/2	9 3/4 248	19 3/4 502	6 152
CA32112 L	46 21	1/2 13	.750 19	200 61	1000 69	1/2	1/2	15 3/4 400	25 3/4 654	12 305
CA32118 L	51 23	1/2 13	.750 19	325 99	1000 69	1/2	1/2	21 3/4 552	31 3/4 806	18 457
CA32122 L	65 29	1/2 13	.750 19	400 122	1000 69	1/2	1/2	25 3/4 654	35 3/4 908	22 559
CA32128 L	69 31	1/2 13	.750 19	500 152	1000 69	1/2	1/2	30 3/4 781	40 3/4 1035	27 686
CA32106 M	42 19	1/2 13	.850 22	100 30	3000 207	1/2	1/2	9 3/4 248	19 3/4 502	6 152
CA32112 M	46 21	1/2 13	.850 22	200 61	3000 207	1/2	1/2	15 3/4 400	25 3/4 654	12 305
CA32118 M	52 24	1/2 13	.850 22	325 99	3000 207	1/2	1/2	21 3/4 552	31 3/4 806	18 457
CA33106 L	41 19	3/4 19	1.075 27	50 15	1000 69	3/4	3/4	9 3/4 248	19 3/4 502	6 152
CA33112 L	46 21	3/4 19	1.075 27	100 30	1000 69	3/4	3/4	15 3/4 400	25 3/4 654	12 305
CA33118 L	51 23	3/4 19	1.075 27	175 53	1000 69	3/4	3/4	21 3/4 552	31 3/4 806	18 457
CA33112 M	47 21	3/4 19	1.188 30	100 30	3000 207	3/4	3/4	15 3/4 400	25 3/4 654	12 305
CA33118 M	51 23	3/4 19	1.188 30	175 53	3000 207	3/4	3/4	21 3/4 552	31 3/4 806	18 457
CH37118 L*	64 29	1 25	1.375 35	100 30	1000 69	1	1	21 3/4 552	31 3/4 806	18 457
CH37122 L*	73 33	1 25	1.375 35	125 38	1000 69	1	1	25 3/4 654	35 3/4 908	22 559
CH37128 L*	77 35	1 25	1.375 35	150 46	1000 69	1	1	30 3/4 781	40 3/4 1035	27 686
Bevel Crank Hose Reels Maximum temperature 210 °F (99 °C)										
BA36112 L	57 26	1/4 6	Twin Welding	250 76	200 14	1/4	1/4	15 3/4 400	25 3/4 654	12 305
BA34112 M	54 24	1/2 13	Twin Hydraulic	100 30	3000 207	1/2	1/2	15 3/4 400	25 3/4 654	12 305
Electric Motor Driven Hose Reels Maximum temperature 210 °F (99 °C)										
EA32106 L10A	61 28	1/2 13	.750 19	100 30	1000 69	1/2	1/2	9 3/4 248	19 5/8 498	6 152
EA32112 L12D	64 29	1/2 13	.750 19	200 61	1000 69	1/2	1/2	15 3/4 400	23 7/8 606	12 305
EA32118 L12D	68 31	1/2 13	.750 19	325 99	1000 69	1/2	1/2	21 3/4 552	29 5/8 752	18 457
EA33112 L12D	68 31	3/4 19	1.075 27	100 30	1000 69	3/4	3/4	15 3/4 400	23 7/8 606	12 305
EA33118 L12D	68 31	3/4 19	1.075 27	175 53	1000 69	3/4	3/4	21 3/4 552	29 5/8 752	18 457
EA33112 M12D	71 32	3/4 19	1.188 30	100 30	3000 207	3/4	3/4	15 3/4 400	23 7/8 606	12 305
EA33128 M12D	91 41	3/4 19	1.188 30	275 84	3000 207	3/4	3/4	30 3/4 781	38 5/8 981	27 686
E13112 M24D	71 32	3/4 19	1.188 30	100 30	3000 207	3/4	3/4	15 3/4 400	23 7/8 606	12 305
EH37118 L12D*	82 37	1 25	1.375 35	100 30	300 21	1	1	21 3/4 552	31 787	18 457
Air Motor Driven Hose Reels Filter, regulator, lubricator required. Maximum temperature 210 °F (99 °C)										
AA32112 L4A	62 28	1/2 13	.750 19	200 61	1000 69	1/2	1/2	15 3/4 400	23 1/4 591	12 305
AA33106 L4A	59 27	3/4 19	1.075 27	50 15	1000 69	3/4	3/4	9 3/4 248	17 1/4 438	6 152
AA33112 L6A	68 31	3/4 19	1.075 27	100 30	1000 69	3/4	3/4	15 3/4 400	23 1/4 591	12 305

Hose assemblies can be quoted upon request. **CAUTION:** To prevent drum damage, fully extend and pressurize hose and rewind on the reel. For metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example CA33112 M70. *All 1" reel models have an 8" (203 mm) diameter drum.

Many more reel models available in addition to chart. Please contact manufacturer for details.

Prop 65: **WARNING:**
Cancer and Reproductive Harm - www.P65Warnings.ca.gov.