

Light/Medium Duty Cord Reels | Series LD / LG / LH




Light/Medium Duty Cord Reels

Reelcraft's new line of light and medium duty cord reels are designed for less strenuous applications in which a capable and long-lasting reel is required. The reels accommodate lengths of 16/3, 14/3, 12/3, and 10/3 diameter cable.

		Dimensions - Size Index							
		1		2		3		4	
		in	mm	in	mm	in	mm	in	mm
A		11 ⁷ / ₈	302	15 ¹ / ₄	387	13 ³ / ₄	349	17 ³ / ₄	451
B		9 ¹ / ₄	235	11 ¹ / ₂	292	11	279	17 ¹ / ₄	438
C		3 ³ / ₄	95	5	127	8 ³ / ₄	222	11 ¹ / ₈	283
D		2 ³ / ₄	98	9 ³ / ₁₆	233	1/4" mounting holes. If reels are to be mounted more than 15' overhead, consult manufacturer.			
E		2	51	3	76				
F		1 ⁷ / ₈	48	5 ¹ / ₂	139				
G		7 ¹ / ₁₆	11	9 ¹ / ₁₆	14				
H		N/A		1 ⁵ / ₈	41				

Series LD Cord Reels




Designed for overhead mounting, these reels are compact, feature a powder coated steel housing, adjustable cable stop and a resettable circuit breaker.

Model with Cord	Cord Ending	Cord Specifications						Volts	Amps	Weight		Size Index #
		AWG	mm	# Cond	ft	m	Type			lbs	kg	
 LD2040 163 2*	Style 2	16	1.33	3	40	12	SJTW	120	0.3	11	5	1
 LD2030 163 9	Style 9	16	1.33	3	30	9	SJTW	125	10	8	4	1
 LD2030 143 9	Style 9	14	2.08	3	30	9	SJTW	125	13	9	4	1

*Requires a minimum of five feet hanging cable (outside reel). Designed for ceiling mount.

Series LG Cord Reels



The medium duty Series LG cord reels are constructed from high-impact resistant composite materials to be lighter and compact. They may be mounted overhead, on a wall or detached from the mounting bracket completely. They also feature an adjustable cable stop and a circuit breaker that can be reset.

Model with Cord	Cord Ending	Cord Specifications						Volts	Amps	Weight		Size Index #
		AWG	mm	# Cond	ft	m	Type			lbs	kg	
 LG3050 163 8*	Style 8	16	1.33	3	50	15	SJTW	120	10	13	6	2
 LG3050 143 9	Style 9	14	2.08	3	50	15	SJTW	125	13	14	6	2
 LG3040 123 9	Style 9	12	3.32	3	40	12	SJTW	125	15	14	6	2

*Requires a minimum of five feet hanging cable (outside reel).

Series LH Hand Crank Reels

Designed with the contractor in mind, Series LH medium duty hand crank reels are portable and deliver power where and when it is necessary. They feature four circuit breaker protected outlets and a corrosion resistant powder coating.

Model with Cord*	Cord Ending	Cord Specifications						Volts	Amps	Weight		Size Index #
		AWG	mm	# Cond	ft	m	Type			lbs	kg	
 LH2080 143	4 Outlets	14	2.08	3	80	24	SJTW	125	10	15	7	3
 LH3100*	4 Outlets	10	5.37	3	100	30	STW	125	15	13	6	4

*Does not include cord

Light cord reels are UL listed for the United States. Power cord reels and hand crank reels are UL listed for United States and Canada.

Cord Options

Style #2

13 watt fluorescent light features a durable shock-resistant lamp holder and shatter-resistant tube with switch.



Style #8

13 watt fluorescent light features an on/off switch on the handle and an outlet.




Style #9

Triple outlet with grounded receptacles. For maximum ratings, consult manufacturer.





Products on this page are warranted for 1 year.

Models listed with an icon can ship same day upon request when the order is received by 11:30 AM Eastern Time for quantities of 5 or fewer.

 Indiana Warehouse

 Indiana & California Warehouses

 California Warehouse

 Canadian Warehouse