



HVAC maintenance
SOLUTIONS

Heating Service Products

Protective maintenance for steam and hot water systems.



RECTORSEAL
A CSW Industrials Company

8-Way™

BOILER WATER CONDITIONER

◀ CONDITIONNEUR D'EAU DE CHAUDIÈRE

- Build alkalinity
- Control pH
- Inhibit corrosion
- Sure-cure color indicator

PROTECTIVE MAINTENANCE FOR STEAM & HOT WATER HEATING SYSTEMS

1 qt. / 946 l

DANGER: Causes severe skin burns and serious eye damage. May be harmful to aquatic life. May be corrosive to metals. See additional precautionary statements on back.
DANGER: Provoque des brûlures cutanées graves et des lésions oculaires graves. Peut être nocif en cas d'ingestion. Peut être corrosif pour les métaux. Voir les mises en garde supplémentaires au verso.

RECTORSEAL
A CSW Industrials Company

Sootspray™

BURNER SOOT REMOVER

◀ DÉCAPANT DE SUIE DE BRÛLEUR

- Prevent insulating soot from forming
- Improve burner efficiency

CONTINUOUS CATALYTIC ACTION KEEPS BURNER SURFACE SOOT FREE

net wt. 14 oz. / 39 kg

DANGER: Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin burns and eye damage. May cause respiratory irritation, and may be harmful to aquatic life. See additional precautionary statements on back.
DANGER: Contient du gaz sous pression; peut exploser sous l'effet de la chaleur. Peut provoquer une irritation respiratoire et une somnolence ou des vertiges. Peut causer des brûlures cutanées graves et des lésions oculaires graves. Peut être nocif en cas d'ingestion. Voir les mises en garde supplémentaires au verso.

RECTORSEAL
A CSW Industrials Company

Odorgon™

FUEL OIL ABSORBER

◀ ABSORBEUR DE MAZOUT

- Eliminate odor
- Remove stains
- Mild fragrance

ABSORB FUEL OIL RESIDUE REMAINING AFTER LEAK OR SPILL CLEANUP

net wt. 14 oz. / 39 kg

DANGER: Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. See additional precautionary statements on back.
DANGER: Provoque une irritation oculaire grave. Nocif en cas d'ingestion. Peut provoquer une irritation respiratoire. Voir les mises en garde supplémentaires au verso.



HEATING CHEMICALS

Performance. Efficiency. Protection.



Protection for today's high efficiency heating systems. Extended life of older systems.

BOILER WATER TREATMENT

Surgemaster™

Boiler surge inhibitor

Code	Description	Qty.
68742	5.3 oz.	12

- FEATURES**
- Will not damage seals and gaskets
 - Inhibits corrosion
 - No petroleum distillates
 - Sure-cure color indicator

APPLICATION • Prevents priming and surging in steam heating systems • Precipitates impurities and promotes efficiency • Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Pour into boiler access point.

RECOMMENDED FOR

- Steam heating systems



8-Way™

Boiler water conditioner

Code	Description	Qty.
68712	1 qt.	12
68714	1 gal.	4
68716	30 gal.	1

- FEATURES**
- Will not damage seals and gaskets
 - Non-chromate; biodegradable
 - No petroleum distillates
 - Sure-cure color indicator

APPLICATION • Builds alkalinity • Controls ph • Removes sludge • Removes rust scale • Inhibits boiler corrosion • Inhibits steam line corrosion • Prevents oxygen pitting • Inhibits lime scale • Prevents surging and foaming • Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Pour directly into boiler or pump into drain valve using force pump.

RECOMMENDED FOR

- Protective maintenance for steam and hot water systems.



30 gallon drum



▲ Force pump drain line injection



BOILER WATER TREATMENT & SEALANT

Surgex™

Boiler surge treatment

Code	Description	Qty.
68752	1-½ oz.	20

FEATURES

- Economical
- Concentrated
- Sure-cure color indicator

APPLICATION • Stops active surging in steam and hot water boilers. • Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Pour into boiler access point.

RECOMMENDED FOR • Steam and hot water systems



Scale Flush Formerly Steamaster

Boiler scale remover

Code	Description	Qty.
68732	36 tablet bottle	12

FEATURES

- Will not damage seals and gaskets
- No petroleum distillates
- Sure-cure color indicator

APPLICATION • Loosens excessive scale • Cleans gauges • Restores efficiency • Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Drop into boiler access point.

RECOMMENDED FOR • Steam and hot water heating systems

Formerly Steamaster



Sealmaster™

Boiler leak sealant

Code	Description	Qty.
68722	1 qt.	12

FEATURES

- Stops corrosion
- Will not damage seals and gaskets
- No petroleum distillates

APPLICATION • Stop active leaks • Fill and seal holes, cracks and loose joints • Provide corrosion inhibiting protective coating • Pour directly into boiler or pump into drain valve using force pump.

RECOMMENDED FOR • Steam and hot water systems



▲ Force pump drain line injection



BURNER SOOT REMOVER & FURNACE CEMENT

Sootspray™

Burner soot remover


Code	Description	Qty.
68342	14 oz. aerosol	12

FEATURES

- Contains no lead
- Cuts vacuum time by 50-100%

APPLICATION • Prevents insulating soot from forming • Continuous safe catalytic action keeps burner surface soot free • Improve burner efficiency • Reaches where vacuum cleaners cannot.

RECOMMENDED FOR • Oil & gas-fired burners



PyroSeal™

Furnace & retort cement

Code	Description	Qty.
68612	1-½ lb.	12
68614	3 lb.	12
68616	6 lb.	8
68618	12 lb.	4

FEATURES

- Shrink-proof, crack-proof
- Contains no asbestos or OSHA restricted fibers

APPLICATION • Seals doors and joints • Smooth, creamy, easy-spreading cement stays where it is applied • For high temperature sealing & bonding

RECOMMENDED FOR • Fire brick • Combustion chambers • Furnace doors • Flue pipes





FUEL OIL DEODORIZERS & ABSORBENTS

Odorgon™ Spray

Code	Description	Qty.
68516	14 oz. aerosol	12

FEATURES

- Non-lingering, mild scent
- Non-flammable

Fuel Oil Neutralizer

APPLICATION • Kills fuel oil odor in hard to reach corners and vertical surfaces

RECOMMENDED FOR

- Neutralizing fuel oil odor remaining after leak or spill cleanup



Odorgon™ Powder

Code	Description	Qty.
68512	1 lb.	12
68514	2 lbs.	12

FEATURES

- Non-lingering, mild scent
- Non-explosive
- Non-flammable

Fuel Oil Neutralizer

APPLICATION • Handy for cleaning up after fuel oil spills and leaks • Sifter top for controlled economical usage and clean storage

RECOMMENDED FOR

- Eliminate fuel oil odor and stains on floors and horizontal surfaces



WATER HEATER FLUSH

Calci-free™

Code	Description	Qty.
68708	1.2 lbs.	12



FEATURES

- Restores circulation in 20 min.
- More effective than vinegar
- Easy to use with no strong odor
- Cleans heat exchanger fast
- Biodegradable

Tankless water heater flush

APPLICATION • Economical cleaner • Restores circulation and pressure in commercial and residential tankless water heaters • Cleans heater coils thoroughly

RECOMMENDED FOR • Routine cleaning to remove calcium and other solid deposits from heating coils in tankless water heaters



Calci-free™ Kit

Code	Description	Qty.
68711	flush kit	1

FEATURES

- A complete cleaning system
- Cleans in only 20 minutes
- Heavy duty, chemical resistant utility pump

Complete tankless water heater flush kit

APPLICATION • Complete system cleans and restores efficiency to tankless water heaters • Includes everything needed to safely and effectively remove scale and mineral deposits

RECOMMENDED FOR • Routine cleaning to remove calcium and other solid deposits from heating coils in tankless water heaters





LEAK LOCATORS

Better Bubble™

Gas leak locator

Code	Description	Qty.
65554	8 oz. - dauber top	12
65432	32 oz. - trigger spray	12
65273	1 gal.	4

FEATURES

- Fast acting
- Long lasting
- Easy to see bubbles
- Continuous bubbling

APPLICATION • Thick formula pinpoints the smallest natural gas, LPG and A/C refrigerant leaks with well defined elastic bubbles that stand up under pressure and windy conditions • Use on surface temperatures from 20° F to 250° F

RECOMMENDED FOR • All types of pipe, tubing, valves, tanks, pressure vessels, condenser and evaporator coils, refrigeration coils, and many other similar applications

Not recommended for oxygen



RectorSeek™ Low-Temp

Low temperature leak locator

Code	Description	Qty.
61273	1 gal.	4

FEATURES

- Longer bubbling action
- Spray application
- Easy to apply

APPLICATION • Leak locator for use on pipes or tanks containing gases at low temperatures • Effective from -35° F to 200° F

RECOMMENDED FOR • All types of pipe (except CPVC), tubing, valves, cylinders, tanks, pressure vessels, condenser and evaporator coils, refrigeration coils and many other similar applications

Not recommended for oxygen



RectorSeek™ Mid-Temp

Mild temperature leak locator

Code	Description	Qty.
60273	1 gal.	4

FEATURES

- Longer bubbling action
- Spray application
- Easy to apply

APPLICATION • Leak locator for use at normal temperature on pipe or tanks that contain gases • Can be used on oxygen, air or gas at temperatures between 40° F to 200° F

RECOMMENDED FOR • All types of pipe, tubing, valves, cylinders, tanks, pressure vessels, condenser and evaporator coils, refrigeration coils and many other similar applications



LEAK REPAIR

EP-200 & 400

Epoxy putty

Code	Description	Qty.
97600	2 oz. EP-200 with display	24
97601	2 oz. EP-200 refill	24
97602	2 oz. EP-200 on blister card	12
97606	4 oz. EP-400 boxed	12



FEATURES

- Mixes like putty
- Hardens in minutes
- Can be drilled, tapped, filed, machined, sanded and painted

APPLICATION • Pre-measured, high-grade epoxy and hardener formulated together in one stick

- Break off the amount needed for each repair
- Bonds to most surfaces

RECOMMENDED FOR • Bonding and filling metals and a variety of other materials



← 97600 counter display

97602 blister card →



Magne-Patch™

Instantly stops small leaks in steel tanks

Code	Description	Qty.
68442	Blister card	12

FEATURES

- Provides temporary repair
- Saves time
- Helps avoid serious spills
- POP Blister Pack

APPLICATION • A powerful, permanent magnet holds a flexible plug against the hole and against existing pressure

- Quickest tank repair available
- Reusable
- Blister packed

RECOMMENDED FOR • For steel tanks holding oil, gasoline, water, and chemicals





PIPE THREAD SEALANTS

RectorSeal No. 5[®]

Code	Description	Qty.
25790	1-¾ oz.	24
25631	¼ pt.	24
25551	½ pt.	24
25431	1 pt.	12
25300	1 qt.	12
25271	1 gal.	4
Canada		
25001	¼ pt.	12
25002	½ pt.	8
25433	1 pt.	12



- FEATURES**
- Soft set / Slow drying
 - Lead free
 - Smooth application
 - 2 year shelf life
 - Certified to NSF/ANSI/CAN 61

Multi-purpose pipe thread sealant

APPLICATION • Lubricates and protects threaded pipe and fittings • Can be pressurized immediately up to 100 psi for piping up to 2" diameter
 • Ideal for a wide variety of fluids and gases, including potable water

- RECOMMENDED FOR**
- Galvanized Steel • Iron
 - Brass • Copper • Aluminum
 - Stainless Steel
 - Polyethylene • RTRP
 - PVC



RectorSeal T Plus 2[®]

Code	Description	Qty.
23710	1-¾ oz.	24
23631	¼ pt.	24
23551	½ pt.	24
23431	1 pt.	12
23391	1 qt.	12
Canada		
23001	¼ pt.	12
23002	½ pt.	8
23435	1 pt.	12
Australia		
23556	3.38 fl. oz. (100 mL) pouch	12
23557	8.45 fl. oz. (100 mL) pouch	8



- FEATURES**
- Non-setting
 - Lead free
 - 2 year shelf life
 - Certified to NSF/ANSI/CAN 61

PTFE enriched pipe thread sealant

APPLICATION • Contains PTFE & synthetic fibers for superior performance • Can be pressurized immediately following application

- RECOMMENDED FOR**
- Galvanized Steel • Iron • Brass • Copper
 - Aluminum • Stainless Steel • Polyethylene
 - RTRP • PVC • CPVC • ABS



A CSW Industrials Company

RECTORSEAL HEATING DIVISION

Through the use of current technology and social media, RectorSeal provides support for all chemicals and mechanical products and tools including:

- Technical information
- Marketing materials
- Product installation training videos
- Product codes
- SDS and product data sheets
- Trade show scheduling

RectorSeal[®]
 2601 Spenwick Drive, Houston, TX 77055
 713-263-8001
 rectorseal.com
 rectorseal.com/heating

All information is believed to be current at the time of printing, but our policy is one of continuous development. RectorSeal makes no warranties, express or implied, as to its accuracy. RectorSeal reserves the right to discontinue, update or change the information at any time without notice or without incurring obligations. RectorSeal[®], the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice.

©2021 RectorSeal. All rights reserved. R50490 04/21

FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with Flowguard Gold[®], Blazemaster[®] and Corzan[®] piping systems and products made with TempRite[®] Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold[®], BlazeMaster[®], Corzan[®] and TempRite[®] are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.