

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

**SPECIALTY
MARKING SPRAYS**

DESCRIPTION AND USES

Rust-Oleum® Specialty Marking Sprays marks the spot in a variety of bright, visible colors. These sprays temporarily adhere to grass, gravel, soil, lumber, concrete, and blacktop and withstand general weathering. The convenient spray-thru cap makes these sprays ideal for many outdoor uses such as marking athletic fields, roadways, landscaping areas, work areas, and more.

PRODUCTS

SKU	Description
1985830	White
1987830	Fluorescent Orange
1988830	Fluorescent Pink
1989830	Fluorescent Green
1991830	Fluorescent Red
1997830	Bright Yellow

PAINTING CONDITIONS

Use outdoors or in a well ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRODUCT APPLICATION

SURFACE PREPARATION

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Invert can and point at ground or floor. Hold can 4-8" from surface to be marked. Press tip sideways to spray paint. Spray using a steady, even stroke to prevent build-up. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 15 minutes and is fully dry in 8 hours. May recoat at any time.

CLEAN-UP

Clean valve by spraying upright for 2-3 seconds after each use. Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

SPECIALTY MARKING SPRAYS

PHYSICAL PROPERTIES

Physical Properties		MARKING SPRAYS
Resin Type		Acrylic Lacquer (Fluorescents) – Modified Alkyd (Non-fluorescents)
Pigment Type		Varies with color
Solvents		Acetone, Aromatic Hydrocarbons, Toluene, Xylene
MIR		0.85 Max
Fill Weight		11 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 6-7 sq.ft./can (0.56-0.63 m ² /can) Approximately 72-84 linear feet @ 1 inch wide
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	15 minutes
	Fully Dry	8 hours
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.