Revision Date: 2/5/2016

# Rust-Oleum Multi Component Product Information Sheet

**AS6586425 AS 6500 System Navy Gray is a multi component product composed of the following individual chemical components:**

| | |
|---|---|
| AS6586425A | FLOOR 1-GLK 2PK AS6500 NAVY GRAY Activator |
| AS6586425B | FLOOR 1-GL 2PK AS6500 NAVY GRAY KIT Base |

SDSs for each component follow this cover sheet.

## Transportation Information

| | Domestic (USDOT) | International (IMDG) | Air (IATA) | TDG (Canada) |
|---|---|---|---|---|
| **UN Number:** | N.A. | 3066 | 3066 | N.A. |
| **Proper Shipping Name:** | Paint Products in Limited Quantities | Paint and Paint Related Products | Paint and Paint Related Products | Paint Products in Limited Quantities |
| **Hazard Class:** | N.A. | 8 | 8 | N.A. |
| **Packing Group:** | N.A. | II | II | N.A. |
| **Limited Quantity:** | Yes | Yes | No | Yes |

**Finished Good Schedule B Harmonized Tariff Code** 3907.30.0000

# Safety Data Sheet

RUST-OLEUM CORPORATION
* Trusted Quality Since 1921 *
www.rustoleum.com

## 1. Identification

**Product Name:** FLOOR 1-GLK 2PK AS6500 NAVY GRAY Activator

**Revision Date:** 2/4/2016

**Product Identifier:** AS6586425A

**Supercedes Date:** New SDS

**Product Use/Class:** Anti-Slip Coating/Activator

**Supplier:** Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA

**Manufacturer:** Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA

**Preparer:** Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

## 2. Hazard Identification

**Classification**

**Symbol(s) of Product**



**Signal Word**
Danger

**GHS HAZARD STATEMENTS**

| | | |
|---|---|---|
| Skin Corrosion, category 1 | H314 | Causes severe skin burns and eye damage. |
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| STOT, single exposure, category 3, RTI | H335 | May cause respiratory irritation. |
| Reproductive Toxicity, category 2 | H361 | Suspected of damaging fertility or the unborn child. |

**GHS LABEL PRECAUTIONARY STATEMENTS**

| | |
|---|---|
| P201 | Obtain special instructions before use. |
| P260 | Do not breathe dust, fumes, gases, mists, vapors, or spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301+P330+P331 | IF SWALLOWED: rinse mouth. Do NOT induce vomiting. |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P310 | Immediately call a POISON CENTER or doctor/physician. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

**GHS SDS PRECAUTIONARY STATEMENTS**

| | |
|---|---|
| P363 | Wash contaminated clothing before reuse. |

## 3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

| Chemical Name | CAS-No. | Wt.% Range | GHS Symbols | GHS Statements |
|---|---|---|---|---|
| Fatty acids, tall-oil, polymers with linoleic acid dimers and tetraethylenepentamine | 68605-86-7 | 25-50 | GHS05 | H314 |
| Tall Oil Fatty Acids, Reaction Products with Tetraethylene Pentamine | 68953-36-6 | 25-50 | GHS07 | H302-312-315-317-319-335 |
| Epoxidized Oleic Acid Reaction Products with TEPA | 68298-14-6 | 2.5-10 | GHS05-GHS07 | H302-312-314 |
| 4-(tert-butyl)-Phenol | 98-54-4 | 2.5-10 | GHS05-GHS08 | H315-318-361 |
| Benzene-1,3-dimethaneamine (MXDA) | 1477-55-0 | 1.0-2.5 | GHS05-GHS06 | H302-312-314-317-330 |
| 1,5-Diamino-2-methylpentane | 15520-10-2 | 1.0-2.5 | GHS05-GHS07 | H302-312-314-332 |

## 4. First-aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

## 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

## 8. Exposure Controls/Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|---|---|---|---|---|---|---|
| Fatty acids, tall-oil, polymers with linoleic acid dimers and tetraethylenepentamine | 68605-86-7 | 50.0 | N.E. | N.E. | N.E. | N.E. |
| Tall Oil Fatty Acids, Reaction Products with Tetraethylene Pentamine | 68953-36-6 | 30.0 | N.E. | N.E. | N.E. | N.E. |
| Epoxidized Oleic Acid Reaction Products with TEPA | 68298-14-6 | 10.0 | N.E. | N.E. | N.E. | N.E. |
| 4-(tert-butyl)-Phenol | 98-54-4 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| Benzene-1,3-dimethaneamine (MXDA) | 1477-55-0 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| 1,5-Diamino-2-methylpentane | 15520-10-2 | 1.0 | N.E. | N.E. | N.E. | N.E. |

**PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

## 9. Physical and Chemical Properties

| | | | |
|---|---|---|---|
| **Appearance:** | Liquid | **Physical State:** | Liquid |
| **Odor:** | Slight Amine | **Odor Threshold:** | N.E. |
| **Relative Density:** | 0.190 | **pH:** | N.A. |
| **Freeze Point, °C:** | N.D. | **Viscosity:** | No Information |
| **Solubility in Water:** | Slight | **Partition Coefficient, n-octanol/ water:** | N.D. |
| **Decompostion Temp., °C:** | N.D. | | |
| **Boiling Range, °C:** | -18 - 308 | **Explosive Limits, vol%:** | 100.0 - 100.0 |
| **Flammability:** | Does not Support Combustion | **Flash Point, °C:** | 96 |
| **Evaporation Rate:** | Slower than Ether | **Auto-ignition Temp., °C:** | N.D. |
| **Vapor Density:** | Heavier than Air | **Vapor Pressure:** | N.D. |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** When heated to decomposition, it emits acrid smoke and irritating fumes.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

**The acute effects of this product have not been tested. Data on individual components are tabulated below:**

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|---|---|---|---|---|
| 68605-86-7 | Fatty acids, tall-oil, polymers with linoleic acid dimers and tetraethylenepentamine | 4340 mg/kg Rat | 5500 | 25 |
| 68953-36-6 | Tall Oil Fatty Acids, Reaction Products with Tetraethylene Pentamine | 1600 mg/kg Rat | 1700 mg/kg Rat | 25 mg/L |
| 68298-14-6 | Epoxidized Oleic Acid Reaction Products with TEPA | 1600 mg/kg Rat | 1700 mg/kg Rat | N.I. |
| 98-54-4 | 4-(tert-butyl)-Phenol | > 2000 mg/kg Rat | 2318 mg/kg Rabbit | N.I. |
| 1477-55-0 | Benzene-1,3-dimethaneamine (MXDA) | 660 mg/kg Rat | 2000 mg/kg Rabbit | 1.34 mg/L Rat |

N.I. - No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

| | Domestic (USDOT) | International (IMDG) | Air (IATA) | TDG (Canada) |
|---|---|---|---|---|
| **UN Number:** | N.A. | 3066 | 3066 | N.A. |
| **Proper Shipping Name:** | Paint Products in Limited Quantities | Paint and Paint Related Products | Paint and Paint Related Products | Paint Products in Limited Quantities |
| **Hazard Class:** | N.A. | 8 | 8 | N.A. |
| **Packing Group:** | N.A. | II | II | N.A. |
| **Limited Quantity:** | Yes | Yes | No | Yes |

## 15. Regulatory Information

### U.S. Federal Regulations:

**CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

**Sara Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

**HMIS RATINGS**

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Health:** | 2* | **Flammability:** | 1 | **Physical Hazard:** | 0 | **Personal Protection:** | X |

**NFPA RATINGS**

| | | | | | |
|---|---|---|---|---|---|
| **Health:** | 2 | **Flammability:** | 1 | **Instability** | 0 |

**VOLATILE ORGANIC COMPOUNDS, g/L:** 0

**SDS REVISION DATE:** 2/4/2016

**REASON FOR REVISION:**

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

# Safety Data Sheet

RUST-OLEUM CORPORATION
* Trusted Quality Since 1921 *
www.rustoleum.com

## 1. Identification

**Product Name:** FLOOR 1-GL 2PK AS6500 NAVY GRAY KIT Base

**Revision Date:** 2/4/2016

**Product Identifier:** AS6586425B

**Supercedes Date:** New SDS

**Product Use/Class:** Anti-Slip Coating/Base

**Supplier:** Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA

**Manufacturer:** Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA

**Preparer:** Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

## 2. Hazard Identification

**Classification**

**Symbol(s) of Product**

Not a hazardous substance or mixture.

**Signal Word**
No Signal Word has been assigned.

## 3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

| Chemical Name | CAS-No. | Wt.% Range | GHS Symbols | GHS Statements |
|---|---|---|---|---|
| Crystalline Silica / Quartz | 14808-60-7 | 10-25 | Not Available | Not Available |
| Aluminum Oxide | 1344-28-1 | 10-25 | Not Available | Not Available |
| Titanium Dioxide | 13463-67-7 | 1.0-2.5 | Not Available | Not Available |
| Propylene Glycol Monomethyl Ether | 107-98-2 | 1.0-2.5 | GHS02-GHS07 | H226-332-336 |

## 4. First-aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

## 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

## 8. Exposure Controls/Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|---|---|---|---|---|---|---|
| Crystalline Silica / Quartz | 14808-60-7 | 25.0 | 0.025 mg/m3 | N.E. | N.E. | N.E. |
| Aluminum Oxide | 1344-28-1 | 25.0 | N.E. | N.E. | 15 mg/m3 | N.E. |
| Propylene Glycol Monomethyl Ether | 107-98-2 | 1.0 | 50 ppm | 100 ppm | N.E. | N.E. |
| Titanium Dioxide | 13463-67-7 | 1.0 | 10 mg/m3 | N.E. | 15 mg/m3 | N.E. |

**PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

## 9. Physical and Chemical Properties

| | | | |
|---|---|---|---|
| **Appearance:** | Liquid | **Physical State:** | Liquid |
| **Odor:** | Mild | **Odor Threshold:** | N.E. |
| **Relative Density:** | 1.941 | **pH:** | N.A. |
| **Freeze Point, °C:** | N.D. | **Viscosity:** | No Information |
| **Solubility in Water:** | Slight | **Partition Coefficient, n-octanol/ water:** | N.D. |
| **Decompostion Temp., °C:** | N.D. | | |
| **Boiling Range, °C:** | -18 - 2,980 | **Explosive Limits, vol%:** | N.A. - N.A. |
| **Flammability:** | Does not Support Combustion | **Flash Point, °C:** | 100 |
| **Evaporation Rate:** | Slower than Ether | **Auto-ignition Temp., °C:** | N.D. |
| **Vapor Density:** | Heavier than Air | **Vapor Pressure:** | N.D. |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** When heated to decomposition, it emits acrid smoke and irritating fumes.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Contact

ACUTE TOXICITY VALUES

**The acute effects of this product have not been tested. Data on individual components are tabulated below:**

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|---|---|---|---|---|
| 14808-60-7 | Crystalline Silica / Quartz | 5500 mg/kg Rat | 5500 | 100 mg/L |
| 1344-28-1 | Aluminum Oxide | >5000 mg/kg Rat | N.I. | N.I. |
| 13463-67-7 | Titanium Dioxide | >10000 mg/kg Rat | 2500 mg/kg | N.I. |

N.I. - No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

| | Domestic (USDOT) | International (IMDG) | Air (IATA) | TDG (Canada) |
|---|---|---|---|---|
| **UN Number:** | N.A. | N.A. | N.A. | N.A. |
| **Proper Shipping Name:** | Not Regulated | Not Regulated | Not Regulated | Not Regulated |
| **Hazard Class:** | N.A. | N.A. | N.A. | N.A. |
| **Packing Group:** | N.A. | N.A. | N.A. | N.A. |
| **Limited Quantity:** | No | No | No | No |

## 15. Regulatory Information

### U.S. Federal Regulations:

**CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Sara Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| Chemical Name | CAS-No. |
|---|---|
| Aluminum Oxide | 1344-28-1 |

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

**HMIS RATINGS**

**Health:** 2* **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X

**NFPA RATINGS**

**Health:** 2 **Flammability:** 1 **Instability** 0

**VOLATILE ORGANIC COMPOUNDS, g/L:** 38

**SDS REVISION DATE:** 2/4/2016

**REASON FOR REVISION:**

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.