

# MiniRester™ HydraRester™ MegaRester™

»» Water Hammer Arrester Buying Information

## Piston Design

Simplicity of design allows for the highest quality and longest life of any arrester type. Endurance tested to 500,000 cycles without failure.

## Made in America

Arresters are made in the USA with all-American copper, brass and stainless steel materials.

## Connection Options

Sioux Chief's unique ability to provide a wide variety of connection options saves the installer time and money, while eliminating costly transition joints.

## Certified

Arresters are certified by ASSE to the ASSE 1010 Standard, satisfying the requirements of all model codes.



CATEGORY	ITEM NO.	DESCRIPTION	NO LEAD	PKG	MIN. QTY.	CASE QTY.
<b>STRAIGHT</b>						
	660-SB	1/2" Male Sweat	✓	B	50	50
	660-S	1/2" Male Sweat, Clamshell	✓	C*	6	6
	660-3SB	3/4" Male Sweat	✓	B	50	50
	660-Q2B	1/2" CTS PDQ™ Push Fitting	✓	B	50	50
	660-Q2	1/2" CTS PDQ™ Push Fitting, Clamshell	✓	C*	6	6
	660-G2B	1/2" MIP Thread	✓	B	50	50
	660-G2	1/2" MIP Thread, Clamshell	✓	C*	6	6
	660-V2B	1/2" CPVC Socket	✓	B	50	50
	660-V82B	1/2" Male CPVC	✓	B	50	50
	660-V82	1/2" Male CPVC, Clamshell	✓	C*	6	6
	660-X2B	1/2" PEX F1807 Crimp	✓	B	50	50
	660-GVPX2B	1/2" Viega® PEX Press	✓	B	50	50
660-WG2B	1/2" PEX F1960 Grip	✓	B	50	50	
<b>TEE</b>						
	660-T22	1/2" Full-slip Female Sweat	✓	B	25	25
	660-HB	3/4" Female Hose Thread × 3/4" Male Hose Thread		B	25	25
	660-H	3/4" Female Swivel Hose Thread × 3/4" Male Hose Thread, Clamshell		C*	6	6
	660-TKB	3/4" Female Swivel Ballcock Nut × 3/4" Male Ballcock Thread		B	25	25
	660-TK	3/4" Female Swivel Ballcock Nut × 3/4" Male Ballcock Thread, Clamshell		C*	6	6
<b>TUB/SHOWER TEE</b>						
	660-TS	1/2" MSWT Open End Branch x 1/2" FSWT	✓	B	25	25
	660-TS8	1/2" × 8" Stub Out × 1/2" Female Sweat	✓	B	25	25
	660-TS88	1/2" × 8" Double Stub Out × 1/2" Female Sweat	✓	B	25	25
	660-TSX	1/2" Male Sweat × 1/2" PEX F1807 Crimp	✓	B	25	25
	660-TSX88	1/2" × 8" Double Stub Out × 1/2" PEX F1807 Crimp	✓	B	25	25
<b>PEX TEE</b>						
	660-GTW2B	1/2" PEX F1960 Grip	✓	B	25	25
	660-GTX2B	1/2" PEX F1807 Crimp	✓	B	25	25
	660-GTX2	3/4" PEX F1807 Crimp, Clamshell	✓	C*	6	6
<b>COMP. TEE</b>						
	660-GTCOB	1/4" O.D. Comp. Tee for Ice Maker Tube	✓	B	25	25
	660-GTCO	1/4" O.D. Comp. Tee for Ice Maker Tube, Clamshell	✓	C*	6	6
	660-GTC1B	3/8" O.D. Comp. Tee for Supply Tube	✓	B	25	25
	660-GTC1	3/8" O.D. Comp. Tee for Supply Tube, Clamshell	✓	C*	6	6
	660-GT	5/8" O.D. Comp. Tee for 1/2" Nom., Clamshell	✓	C*	6	6
	660-GTB	5/8" O.D. Comp. Tee for 1/2" Nom. Copper Tube	✓	B	25	25
<b>FEMALE COMP. TEE</b>						
	660-GTROB	1/4" O.D. Comp. × 1/4" O.D. Female Comp.	✓	B	25	25
	660-GTRO	1/4" O.D. Comp. × 1/4" O.D. Female Comp., Clamshell	✓	C*	6	6
	660-GTR1B	3/8" O.D. Comp. × 3/8" O.D. Female Comp.	✓	B	25	25
	660-GTR1	3/8" O.D. Comp. × 3/8" O.D. Female Comp., Clamshell	✓	C*	6	6
	660-GTRB	5/8" O.D. Comp. × 5/8" O.D. Female Comp.	✓	B	25	25
	660-GTR	5/8" O.D. Comp. × 5/8" O.D. Female Comp., Clamshell	✓	C*	6	6

Packaging: B = Bulk C = Cut Case \* Individually Bar-Coded

CATEGORY	ITEM NO.	CONN SIZE	UNIT SIZE	LENGTH	WIDTH	FIXTURE VALUE	CUBIC INCH VOLUME	<b>NO LEAD</b>	PKG	MIN QTY.	CASE QTY.
<b>MIP THREAD</b>											
	652-A	1/2"	A	6-1/2"	1-3/8"	1-11	5		B	1	16
	653-B	3/4"	B	8-3/4"	1-3/8"	12-32	7		B	1	16
	654-C	1"	C	11"	1-3/8"	33-60	11		B	1	16
	655-D	1"	D	10-1/8"	2-1/8"	61-113	20		B	1	4
	656-E	1"	E	12-5/8"	2-1/8"	114-154	29		B	1	4
	657-F	1"	F	15-1/8"	2-1/8"	155-330	36		B	1	4
<b>MALE SWEAT/PRESS FITTING</b>											
	652-AS	1/2"	A	8-1/2"	1-3/8"	1-11	5		B	1	16
	653-BS	3/4"	B	10"	1-3/8"	12-32	7		B	1	16
	654-CS	1"	C	12-1/2"	1-3/8"	33-60	11		B	1	16
<b>CPVC SOCKET ASTM D 2846**</b>											
	652-AC	1/2"	A	7-1/2"	1-3/8"	1-11	5		B	1	16
	653-BC	3/4"	B	9-1/2"	1-3/8"	12-32	7		B	1	16
	654-CC	1"	C	12"	1-3/8"	33-60	11		B	1	16
<b>ASTM F1807 PEX CRIMP &amp; ASTM F1960 PEX GRIP**</b>											
	652-AX	1/2"	A	6-1/2"	1-3/8"	1-11	5		B	1	16
	653-BX	3/4"	B	8-3/4"	1-3/8"	12-32	7		B	1	16
	654-CX	1"	C	11"	1-3/8"	33-60	11		B	1	16
	652-AWG	1/2"	A	6-1/2"	1-3/8"	1-11	5		B	1	16
	653-BWG	3/4"	B	8-3/4"	1-3/8"	12-32	7		B	1	16
	654-CWG	1"	C	11"	1-3/8"	33-60	11		B	1	16

\*\*NOTE: PEX and CPVC connection specifications are limited to those called out in their respective ASTM Standards for Fittings.

CATEGORY	ITEM NO.	CONNECTION SIZE AND TYPE	HEIGHT	CUBIC INCH VOLUME	PKG	MIN QTY.	CASE QTY.
<b>COPPER</b>							
	658-1503	3" MIP (ANSI B1.20.1)	23.25"	150	B	1	1
	658-2002	2" MIP (ANSI B1.20.1)	29.25"	200	B	1	1
	658-2004	4" MIP (ANSI B1.20.1)	24.50"	200	B	1	1
	658-4004	4" MIP (ANSI B1.20.1)	42.50"	400	B	1	1
	658-4004F2	4" Class 150 Flange (ANSI B16.24)	41.75"	400	B	1	1
<b>STAINLESS STEEL</b>							
	658S2002	2" MIP (ANSI B1.20.1)	24.25"	200	B	1	1
	658S2004F2	4" Class 150 Flange (ANSI B16.24)	24.00"	200	B	1	1
	658S4004F2	4" Class 150 Flange (ANSI B16.24)	40.00"	400	B	1	1

**TAKE THE FIELD.**



24110 South Peculiar Drive  
Peculiar, Missouri 64078  
P 1.800.821.3944  
F 1.800.758.5950

**DISTRIBUTED BY**

Visit [www.sioxchief.com](http://www.sioxchief.com) for up-to-date prices.

C.10/16 #LT1-WHA-BG

