

Part No: HTS3S-288C

Schedule 80 PVC & CPVC

Hot-Tap Saddle

Desc: 2-1/2X3/4 CPVC HOT TAP SDL FKM SS CUTTER

MSRP: 743.49

Part Code: 050

Weight(lbs): 2.066

Weight(kg): 0.937

Weight(gm): 937

Size: 2-1/2 X 3/4 SOC(1"SPG)

Color: GRAY

Material: CPVC



H2 = 1-3/4

M = 2

L1 = 4-1/8

G1 = 1

H = 6-9/16

H1 = 2

L = 4-1/8

G = 3-15/16

Connection Saddle x Socket (Spigot) - LEAD FREE

Hardware SS316

O-Ring FKM

Cutter SS316

Type Hot-Tap

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch


L = Overall length of fittings; ± 1/16 inch.

M = Outside diameter of socket/thread hub; ± 1/16 inch.

N = Socket bottom to socket bottom; couplings; ± 1/16 inch.

W = Height of cap; ± 1/16 inch

Typical Molded Dimension References



The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained therefrom. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006