

Part No: HTS3S-251C

Schedule 80 PVC & CPVC

Hot-Tap Saddle

Desc: 2X1-1/2 CPVC HOT TAP SADDLE FKM SS CUTTR

MSRP: 1029.08

Part Code: 050

Weight(lbs): 2.273


Weight(kg): 1.031

Weight(gm): 1031

Size: 2 X 1-1/2 SOC(2"SPG)

Color: GRAY

Material: CPVC



L = 2-7/16

G = 4-1/2

G1 = 1-1/4

H = 8-1/2

H1 = 2-11/16

H2 = 1-1/2

M = 2-7/8

L1 = 3-7/16

Connection Saddle x Socket (Spigot) - LEAD FREE

Hardware SS316

O-Ring FKM

Cutter SS316

Type Hot-Tap

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch

L = Overall length of fittings; ± 1/16 inch.

M = Outside diameter of socket/thread hub; ± 1/16 inch.

N = Socket bottom to socket bottom; couplings; ± 1/16 inch.

W = Height of cap; ± 1/16 inch

Typical Molded Dimension References

