Spears® Technical Information

17-Aug-21 09:47:23 PM


Part No: 856-160CF Fabricated Fittings Flanges and Cut in Kits

Desc: 16 CPVC V/S FLANGE SPIGOT CL150 FAB

MSRP: 6404.38 Part Code: 097

Weight(lbs): 66.183 Weight(kg): 30.02 Weight(gm): 30020 Size: 16 Color: GRAY Material: CPVC

Joint Style IPS
Connection Spigot
Ring Plastic



 $\begin{array}{ccc} \textbf{Bolt} &=& 21\text{-}1/4 \\ \textbf{Circle} & \end{array}$

Bolt Size = 1

O.D. = 23-1/2

 $\begin{array}{c} \textbf{No of} = 16 \\ \textbf{Bolts} \end{array}$

L = 17-13/16

Dia. N = 8-9/16 R = 2-3/8

Fabricated Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

H = Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14" & larger inch

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14° & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


W = Height of cap; $\pm 1/4$ inch.

Typical Fabricated Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006