Part No: S1580C07F Valves Swing & Spring Check

Desc: 3/4 PVC CL UTILITY SPR CHK VLV THD EPDM

MSRP: 64.34 Part Code: 026


Weight(lbs): 0.346 Weight(kg): 0.157 Weight(gm): 157
Size: 3/4" Color: CLEAR Material: PVC

Type Utility Spring Check

Connection Fipt **Body Color** Clear

Pressure Rating 150 psi @ 73° F Full Flow (Open)

75 psi Back Pressure (Closed)



A = 1-3/8

 $\mathbf{B} = 2 - 1/16$

C = 4 - 1/16

 $\mathbf{D} = 2 - 5/8$

Fabricated Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

H = Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14" & larger inch

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14'' & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


W = Height of cap; $\pm 1/4$ inch.

Typical Fabricated Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006