

Part No: S1780C30

Valves

Swing & Spring Check

Desc: 3 PVC CL TU UTILITY SPG CHK VLV SOC EPDM

MSRP: 192.29

Part Code: 026

Weight(lbs): 5.556

Weight(kg): 2.52

Weight(gm): 2520

Size: 3"

Color: CLEAR


Material: PVC

Type Utility Spring Check

Connection Socket (TU)

Body Color Clear

Pressure Rating 150 psi @ 73° F Full Flow (Open)
75 psi Back Pressure (Closed)



A = 6-13/16

B = 7-7/16

C = 11-3/16

D = 5-11/16

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch

L = Overall length of fittings; ± 1/16 inch.

M = Outside diameter of socket/thread hub; ± 1/16 inch.

N = Socket bottom to socket bottom; couplings; ± 1/16 inch.

W = Height of cap; ± 1/16 inch

Typical Molded Dimension References

