

OPTIONS

Flush Volume

- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)

Water Efficiency

- High Efficiency
- Low Consumption

Bypass

- Dual-Filtered Fixed Bypass Diaphragm (DFB)

Bumper

- Angle Stop (YO)

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- UL Certified
- cUPC Certified
- BREEAM Water Credit
- CalGreen Compliant
- Green Globes Water Credit
- LEED V4 Water Efficiency Credit
- WaterSense Listed
- cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard SLOAN 113 ESS Hardwired shown

DESCRIPTION

Sloan® Exposed Sensor Water Closet Flushometer

FEATURES

- Sensor-activated, hardwired closet flushometer
- High Chloramine Resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Diaphragm with Linear Filtered Bypass and Vortex Cleansing
- Adjustable tailpiece
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Additional Downloads](#)

VIDEOS

-  ESS Flushometer