

Royal® Flushometer 186-1.5 H

▶ Code Number

3012628

▶ Description

Exposed Urinal Flushometer, for 34" top spud urinals.

► Flush Cycle

3.5 gpf/13.2 lpf

▶ Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Spud Coupling and Flange for 3/4" Top Spud
- Sweat Solder Adapter with Cover Tube & Cast Wall Flange with Set Screw
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- Flush accuracy controlled by CID® technology

3/4" I.P.S. Screwdriver Bak-Chek® Angle Stop w/ Free Spinning Vandal Resistant Stop Cap

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

▶ Variations

H - Inlet on front of valve


Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories

▶ Fixtures

Consult factory for matching Sloan brand fixture options.





► Compliance & Certifications



Made In The USA



This space for Architect/Engineer Approval