

Royal® Top Spud Wall Hung Toilet Fixture WETS-2450.1001 ST-2459 & Royal 111-1.28

Code Number

24501001

Description

Complete HET system with exposed manual Royal $\ensuremath{\mathbb{B}}$ Flushometer and vitreous china wall hung fixture.

► Flush Cycle

Model WETS-2450.1001-1.28 (1.28 gpf/4.8 Lpf)

Specifications

Quiet, exposed, diaphragm type, chrome plated closet Flushometer for either left or right hand supply and vitreous china wall hung water closet with the following features:

FLUSHOMETER

- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Free Spinning Vandal Resistant Stop Cap
- Spud Coupling and Flange for 1-1/2" Top Spud
- Sweat solder adapter with cover tube and cast wall flange with set screw
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush accuracy controlled by CID® technology
- Stop Seat and Vacuum Breaker molded from PERMEX® Rubber
 Compound for Chloramine Resistance

Valve Body, Cover and Tailpiece shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

FIXTURE

- Wall hung vitreous china elongated bowl
- Siphon jet flushing action
- 1-1/2" I.P.S. top spud inlet
- 2 1/8" fully glazed trapway diameter
- Mounting hardware, carrier and toilet seat not included
- Compatible with toilet seat models: Bemis 1955CT, Bemis 2155CT
- Water closet shall be in compliance to the applicable sections of ASME A112.19.2/CSA B45.1
- Compliant with Buy American Act when purchased as a combination

Plumbing System Requirements

Minimum Operating Pressure: 25 PSI

Maximum Fixture Operating Pressure: 80 PSI


Minimum Operating Flow Rate: 18 GPM


All vitreous china dimensions shown in these drawings are nominal. Dimensions can vary wihin the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. Please take this into consideration when planning rough-in and plumbing layouts.


Compliance & Certifications











Finished Floor

This space for Architect/Engineer Approval