

**OPTIONS**

**Flush Volume**

- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)

**Wall Plate Finish**

- Stainless Steel (BSS)
- Polished Chrome (CP)

**Water Efficiency**

- High Efficiency
- Low Consumption

**Bypass**

- Dual-Filtered Fixed Bypass Diaphragm (DFB)

**Override**

- Electrical (OR)
- True Mechanical (TMO)

**Wall Box**

- Front Accessible
- Small (SWB)
- With (W/BOX)

**Compliances & Certifications**

- ADA Compliant
- BAA Compliant
- UL Certified
- cUPC Certified
- CalGreen Compliant
- WaterSense Listed
- cUPC Green Certified
- BREEAM Water Credit
- Green Globes Water Credit
- LEED V4 Water Efficiency Credit

**NOTES**

For product line drawings, [view model-specific spec sheets](#).  
All information contained within this document subject to change without notice.



Image for a standard SLOAN 153 ESS Hardwired shown

**DESCRIPTION**

Sloan® Concealed Sensor Water Closet Flushometer

**FEATURES**

- Sensor-activated, hardwired closet flushometer
- High Chloramine Resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [Additional Downloads](#)

**VIDEOS**

- [ESS Flushometer](#)