

### **CODE NUMBER**

3365367BT

### DESCRIPTION

Box Transformer Power Supply, Below Deck Manual Mixing Valve, Polished Chrome Finish, 2.2 gpm, Laminar Spray, Infrared Sensor, Smart Faucet, Optima® Hardwired-Powered Wall-Mounted Gooseneck Body Faucet.

### **DETAILS**

• Flow Rate: 2.2 gpm (8 Lpm) (2.2GPM)

Spray Type: Laminar (LAM)
Sensor Type: Infrared (IR)
Mounting Type: Single Hole

• Power Supply: Box Transformer (BOX)

• Temperature Mixer: Below Deck Manual Mixing Valve (BDM)

Finish: Polished Chrome (CP)
Factory Default Timeout: 30s
Factory Default GPC: 1.1

### **FEATURES**

Commercial Grade Faucet, ADA Compliant, Cast Brass Spout, Quick Connect Fittings, Integrated Water Shut-off, Wireless Settings Adjustment, On-demand or Metered activation, Hygienic Line Flush, Water Usage and Battery Strength Reporting, Self-adapting Sensor

### **ELECTRICAL SPECIFICATIONS**

• Battery Life: 3 years 8,000 cycles/month

o Optional power harvesting significantly extends service life

• Self-Adjustment Range: 0" (0mm)

• Sensor Range: 0" (0mm)

• Timeout Adjustment Settings: 30s

## **POWER SUPPLY OPTIONS**

• 6VDC Plug Adapter (included with PLG models)

• 6VDC Ganged Adapter Kit (up to 6 units)(sold separately)

• 24VAC Box Transformer (included with BOX models)

## **VIDEOS**


Optima Faucet App

Sloan Optima Below Deck Faucet

## **DOWNLOADS**

- Optima Smart Faucet Below Deck Installation Instructions
- Trim Plates Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- ETF-500/500-S and EBF-550/550-S Below Deck Repair and Maintenance Guide
- Additional Downloads





# **COMPLIANCES & CERTIFICATIONS**



ASME













(ADA Compliant, ASME A112.18.1 Compliant, cUPC Certified, cUPC Low Lead Compliant, Proposition 65, TAS, UL Certified, UPC Certified, UPC Low Lead Compliant)

# RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

## **NOTES**

All information contained within this document subject to change without notice.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com




Looking for other variations of the ETF-500 product? View the general spec sheet with all options.


Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.


## **WARRANTY**

3 Year

# **ROUGH-IN**







Double Inlet Filter Fitting

Single Inlet Filter Fitting Kit with Below Deck Manual Mixing Valve (BDM)

Single Inlet Filter Fitting Kit with Below Deck Thermostatic Mixing Valve (BDT)

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com