

# **Sloan® Flushometers 111**

## ▶ Code Number

3780034

## Description

Exposed Water Closet Flushometer, for floor mounted or wall hung top spud bowls.

## ► Flush Cycle

1.6 gpf/6.0 Lpf

## ▶ Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer for left or right hand supply with the following features:

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- Spud Coupling and Flange for 11/2" Top Spud
- Spud Coupling and Flange for 11/2" Top Spud
- Sweat Solder Adapter with Cover Tube & Cast Wall Flange with Set Screw
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID Technology
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance
- 1" I.P.S. Screwdriver Bak-Chek® Stop with free spinning vandal resistant stop cap

Valve Body, Cover and Tailpiece shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

## ► Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.


## ▶ Fixtures

Consult factory for matching Sloan brand fixture options.

## Variations

See Variation Section of the Sloan Catalog for details on these and other Flushometer accessories.





► Compliance & Certifications

Made In The USA





This space for Architect/Engineer Approval