Part No: 1822-040BL Low Extractable Valves

Desc: 4 PVC LE TU2K IND BALL VALVE SOC EPDM

MSRP: 1870.02 Part Code: 066

Weight(lbs): 13.488

Size: 4"


Weight(kg): 6.118 Weight(gm): 6118 Color: BLUE Material: PVC LE

Type TU 2000 Ind Ball Valve

Connection Socket

O-Ring EPDM

Pressure Rating 235 psi @ 73° F



 $\mathbf{A} = 7-3/4$

C = 11-7/8

 $\mathbf{D} = 6 - 3/4$

E = 9

Cv = 2865Values

Injection Molded Dimension References:

(LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; $\pm 1/32$ inch.

= Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/32$ inch


= Overall length of fittings; $\pm 1/16$ inch.


M = Outside diameter of socket/thread hub; $\pm 1/16$ inch.


= Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.


 $W = \text{Height of cap}; \pm 1/16 \text{ inch}$

Typical Molded Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 -EAST COAST: (717) 938-9006