

Part No: 4251-015

FlameGuard®

Flange

Desc: 1-1/2 CPVC FG SOLID FLANGE SOC CL150

MSRP: 14.99

Part Code: 070

Weight(lbs): 0.518

Weight(kg): 0.235

Weight(gm): 235

Size: 1-1/2"


Color: ORANGE

Material: CPVC

Type Flange - One Piece

Connection Socket

Pressure Rating 175 psi (1.21 Mpa) @ 150° F



L = 1-5/8

M = 2- 1/2

N = 3/16

R = 23/32

No of Bolts = 4

Bolt Circle Dia. = 3-7/8

Bolt Size = 1/2

Min. Bolt Length = 2-1/2

Max. O.D. = 5-1/16

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch


L = Overall length of fittings; ± 1/16 inch.

M = Outside diameter of socket/thread hub; ± 1/16 inch.

N = Socket bottom to socket bottom; couplings; ± 1/16 inch.

W = Height of cap; ± 1/16 inch

Typical Molded Dimension References



The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained therefrom. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006