8/11/2020 XtraExport

Spears® Technical Information

11-Aug-20 05:37:23 AM

Connection Flanged O-Ring FKM Connection Flanged O-Ring FKM Cv = 13000 Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. I = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
MSRP: 39913.59 Weight(lbs): 175.453 Size: 16" Color: GRAY Material: CPV Connection Flanged O-Ring FKM Cv = 13000 Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch.	Part No: 5433-160C	Valves	Butterfly Check Valve	
Weight(lbs): 175.453 Size: 16" Color: GRAY Material: CPV Connection Flanged O-Ring FKM Color: GRAY O-Ring FKM Connection Flanged O-Ring FKM Color: GRAY Color: GRAY Material: CPV Connection Flanged O-Ring FKM Color: GRAY Color: GRAY Material: CPV Color: GRAY Material: CPV Color: GRAY Material: CPV Color: GRAY Color: GRAY Material: CPV Color: GRAY Material: CPV Color: GRAY Color: GRAY Color: GRAY Material: CPV Color: GRAY Color: GRAY Material: CPV Color: GRAY Material: CP	Desc: 16 CPVC BUTTERFLY CH		•	
Size: 16" Color: GRAY Material: CPV Connection Flanged O-Ring FKM Cv = 13000 Values Size: 16" Cv = 13000 Values Size: 16" Cv = 13000 Note: 10	MSRP: 39913.59	Part Cod	Part Code: 290	
Connection Flanged O-Ring FKM Cv = 13000 Values njection Molded Dimension References: (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting, 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.	Weight(lbs): 175.453	Weight(kg): 79.584	Weight(gm): 79584	
O-Ring FKM Cv = 13000 Values Injection Molded Dimension References: (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.	9 , /	Color: GRAY	Material: CPVC	
O-Ring FKM Cv = 13000 Values Injection Molded Dimension References: (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.		Connection Florand		
A = 21-1/4 B = 23-1/2 Cv = 13000 Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.		O-Ring FRIM		
Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values njection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. G = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. G = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values njection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. G = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. G = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values njection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. G = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. G = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values njection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. G = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. G = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
Values Injection Molded Dimension References: G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.				
(LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.	A = 21-1/4 $B = 23-$			
G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses inch. H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch. J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch. L = Overall length of fittings; ± 1/16 inch. M = Outside diameter of socket/thread hub; ± 1/16 inch. N = Socket bottom to socket bottom; couplings; ± 1/16 inch.	njection Molded Dimension Ro	eferences:		
 Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1/16 inch. Socket bottom to socket bottom; couplings; ± 1/16 inch. 	(LAYING LENGTH) intersection		90° elbows, tees, crosses; $\pm 1/3$	
 Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1/16 inch. Socket bottom to socket bottom; couplings; ± 1/16 inch. 	H = Intersection of center lines to face	e of fitting; 90° elbows tees, crosses; $\pm 1/32$	2 inch.	
 Overall length of fittings; ± 1/16 inch. Outside diameter of socket/thread hub; ± 1/16 inch. Socket bottom to socket bottom; couplings; ± 1/16 inch. 				
 Outside diameter of socket/thread hub; ± 1/16 inch. Socket bottom to socket bottom; couplings; ± 1/16 inch. 				
N = Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.				
1 0				
$W = Height of Cab. \pm 1/10 High$		couplings, ± 1/10 men.		
	$N = \text{Height of cap}; \pm 1/16 \text{ inch}$			
Typical Molded Dimension References	Sypical Molded Dimension Ref	<u>erences</u>		

The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006